
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.


2003, Projecta Unlimited Inc.


SPECIFICATIONS

| PARAMETERS | VALUES | UNITS |
|-----------------------------|----------------|-------|
| RATED VOLTAGE (SQUARE WAVE) | 3.6 | Vp-p |
| OPERATING VOLTAGE RANGE | 2.5 ~ 4.5 | Vp-p |
| RATED CURRENT (MAX) | 90 | mA |
| COIL RESISTANCE | 15±3 | ОНМ |
| MINIMUM SPL @ 10 CM | 87 | dBA |
| RESONANT FREQUENCY | 2,500±500 | Hz |
| OPERATING TEMPERATURE | −30 ~ +70 | ċ |
| STORAGE TEMPERATURE | -40 ~ +85 | ċ |
| HOUSING MATERIAL | LCP | - |
| TERMINAL MATERIAL | TIN PLATED PBS | - |
| WEIGHT | 0.42 | grams |
| | | |

| I | | REVISIONS | | |
|---|-----|-----------------------------------|---------|----------|
| I | LTR | DESCRIPTION | DATE | APPROVED |
| I | _ | RELEASED FROM ENGINEERING | 1/4/05 | |
| I | Α | CHANGED MAT. & TERM. MAT. | 3/9/05 | G.V. |
| I | В | REMOVED LEAD FREE ADDED ROHS NOTE | 8/10/05 | |
| I | С | ADDED RESONANT FREQ. TOLERANCE | 5/16/07 | R.W. |








NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.



| UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3. | | projects ® unlimited Dayton , Ohio | | | | |
|---|------|------------------------------------|---------------------------------|--|-----------|-----|
| | | TRANSDUCER(ELECTRO-MECH) | | | | |
| APPROVALS | DATE | SMT-0825-T-R | | | | |
| DRAWN R.A.C. | 1/05 | | | | | |
| APPROVED ₹. ₩. | 1/05 | SIZE A | SIZE DRAWING NO. A SMT-0825-T-R | | | |
| | | А | 3M1-0623-1-R | | | -17 |
| DO NOT SCALE DRAW | VING | SCALE: N.T.S. | | | SHEET 1 0 | F 1 |

SMT-0825-T-R.DWG