
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.


© 2005, Projects Unlimited Inc.


**SPECIFICATIONS** 

	REVISIONS		
LTR	DESCRIPTION	DATE	APPROVED
_	RELEASED FROM ENGINEERING	9/12/05	

PARAMETERS	VALUES	UNITS	
RATED VOLTAGE	12	Vp-p	
OPERATING VOLTAGE RANGE	3 ~ 28	Vp-p	
RATED CURRENT (MAX)	7	mΑ	
CAPACITANCE	25,000±30%	рF	
MINIMUM SPL @ 10 CM	92	dBA	
RESONANT FREQUENCY	2,800±500	Hz	
OPERATING TEMPERATURE	−30 ~ +85	°C	
STORAGE TEMPERATURE	-40 ~ +95	°C	
HOUSING MATERIAL	ABS	=	
TERMINAL MATERIAL	Au PLATED PHOSPHER BRONZE	-	
WEIGHT	11.7	grams	







## NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/ 95/EC COMPLIANT.

APPROVALS DATE

DRAWN J.A.F. 9/05

CHECKED E.P. 9/05

APPROVED B.R. 9/05

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN
MILLIMETERS, TOLERANCES ARE ±0.5 AND
ANGLES ARE ±3".

TRANSDUCER (PIEZO)

projects ® unlimited

FILE NAME AT-4228-TWT-F-R.DWG APPROVED B.R. 9/0. DO NOT SCALE DRAWING

AT-4228-TWT-F-R

Dayton , Ohio

SCALE: N.T.S. SHEET 1 OF