





9615 SW Allen, Suite 103
 Beaverton, OR 97005
 Phone: (503) 643-4899
 800-275-4899
 Fax: (503) 372-1266
 Website: www.cui.com

Specifications

| | | | | | |
|----|--------------------|----------------------------------|---------------------|-----------------------|-------------------|
| 1 | Part No. | GF0778B | | | |
| 2 | Nominal Size | 77 mm. | 3" | inch | |
| 3 | Impedance | 8 Ω \pm 15% | at | 800 Hz. | 1 V. |
| 4 | Resonance | 250 Hz. \pm 50 Hz. | FO Hz. | 1 V. | |
| 5 | S.P. Level | 95 dB/W | 3 dB | 1 w. | 50 cm. average at |
| 6 | Response | fo Hz. \sim 15K Hz. | MAX 10dB | 500, 600, 800, 1K Hz. | |
| 7 | Crossover Freq. | Hz. | Hz. | dB/OCT | Net work |
| 8 | Input Power | Nominal Input | 3 w. | Handling Capacity | 5 w. |
| 9 | Operation | Must be normal at program source | | | 3 w. |
| 10 | Buzz, Rattle, etc. | Must be normal at sine wave | | | 4.89 v. |
| 11 | Flux Density | Gauss \pm 10% | | | |
| 12 | Total Flux | Max well min | | | |
| 13 | Magnet | Size | 45 x 22 x 8 mm | gr | oz |
| 14 | Total Weight | gr oz | | | |
| 15 | Load Test | After test meet item 9 and 10 | White noise | 3 W. | 48 Hours |
| 16 | Distortion | % MAX | | Hz | W. |
| 17 | Heat Test | After test meet item 9 and 10 | 70 \pm 2 \pm °C | 20-50 %R.H. | 48 Hours |
| 18 | Humidity Test | After test meet item 9 and 10 | 40 \pm 2 \pm °C | 90-95 %R.H. | 48 Hours |

| | | | |
|-----------|---------|----------|--------|
| PART NO. | GF0778B | UNITS: | mm |
| DRAWN BY: | | PAGE NO: | 1 of 2 |

4 - 5 ± 0.1 mm



9615 SW Allen, Suite 103
Beaverton, OR 97005
Phone: (503) 643-4899
800-275-4899
Fax: (503) 372-1266
Website: www.cui.com

TITLE:

PART NO.

GF0778B

UNITS:

mm

DRAWN BY:

APPROVED BY: