

	Date	SYM	REVISION RECORD	AUTH	DR.	CK.
	10/22/05	Α	ADDED "ROHS COMPLIANT"	T.B.	B.S.	
	5/02/08	В	ADDED NOTE.	T.B.	B.S.	
1						

NOTE:

ORIENTATION OF SNAPS AND WIRES VARIES AND IS SHOWN FOR REFERENCE ONLY. RED WIRE TO POSITIVE CONTACT. BLACK WIRE TO NEGATIVE CONTACT.

ROHS COMPLIANT

N0.	PART NAME	MATERIAL	QTY.	Tolerance	M	Memory Prote		ction Devices, Inc	
1	COVER	PVC COVER OVER FIBERBOARD	1	(Except as noted)		200	Broad Hollow Road, Farmingdale, New York 11735		ale. New York 11735
2	BLACK WIRE(-)	24 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	decimal		Scale Drawn By B.S. Approved By T.B. Title 9 VOLT BATTERY SNAP-I STYLE, HEAVY DUTY,		Scale	Drawn By B.S.
3	RED WIRE (+)	24 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	1.5 (000)					
4	FEMALE SNAP	PHOSPHOR BRONZE, NICKLE PLATED, HEAVY DUTY	1	±.5 (.020)					Approved By T.B.
5	MALE SNAP	BRASS NICKLE PLATED	1	Fractional	Title				
			± .8 (.030)	12" WIRE LEADS					
			Angular	Date		Drawing Number			
			± 3°	5/02,	/08 BS12I-HD			PI-HD	