

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
10/22/05	А	ADDED "ROHS COMPLIANT"	T.B.	B.S.	
5/02/08	В	ADDED NOTE	T.B.	B.S.	

NOTE:

ORIENTATION OF SNAPS AND WIRES VARIES AND IS SHOWN FOR REFERENCE ONLY. RED WIRE TO POSITIVE CONTACT. BLACK WIRE TO NEGATIVE CONTACT.

ROHS COMPLIANT

N0.	PART NAME	MATERIAL	QTY.	Tolerance	M)	Mem	mory Protection Devices, Inc			
1	COVER	PVC COVER OVER FIBERBOARD	1	(Except as noted)	(\square)	200 Broad Hollow Road, Far		d, Farmingd	mingdale, New York 11735	
2	BLACK WIRE(-)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	decimal				Scale	Drawn By B.S.	
3	RED WIRE (+)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	±.5 (.020)						
4	FEMALE SNAP	BRASS, NICKLE PLATED	1	,					Approved By T.B.	
5	MALE SNAP	BRASS NICKLE PLATED	1	Fractional	Title					
				± .8 (.030)		9 VOLT BATTERY SNAP-I STYLE-6" WIRE LEA			YLE-6" WIRE LEADS	
				Angular	Date		Drawing Number			
		± 3°	5/02,	/08	BS6I					