PRODUCT DATASHEET

NiMH Battery Charger (CHFM)

Asia Pacific Region

Download Instructions

SAFE

• Safety on/off switch



EASY

 Convenient displays tell when charge is complete



ECONOMICAL

 Batteries can be charged hundreds of times



Before Using Your Charger:

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Easy Charger



Product Detail:

Designation: Easy Charger - Asia Pacific Region

Color: Gun Metal Gray with Pearl Face Plate

Charge Capability: "AA" (2) or (4)

"AAA" (2) or (4)

"AA" (2) and "AAA" (2) Simultaneously

Charging Time: (estimate)

L	Battery	Capacity	Estimated
I	(NiMH)	(mAh)	(time)
	AA	2650	9.0 hrs
	AA	2500	8.5 hrs
	AA	2000	7.0 hrs
	AAA	1000	10.0 hrs
Γ	AAA	900	9.0 hrs
	AAA	700	7.0 hrs

Shutoff Mechanism: Delta V Detection

Timer (10 hours \pm 30 minutes)

Temperature detection at 55° C Charging Current: AA @ DC 2.8V, $360\text{mA} \pm 10\%$

AAA @ DC 2.8V, 120mA ± 10%

Trickle Charge: None

Input Rating: Universal Voltage: 100-240vac, 50/60Hz Input Current: Maximum 150mA at AC 120V/60Hz

Input Power: ≤ 6W

Typical Weight: 166.5 grams (5.9 oz.)

Dimensions (mm): 133 x 89 x 32 (H x L x W)

Rev Polarity Protection: Yes Primary Battery Detection: Yes

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

©Energizer

Contents herein do not constitute a warranty.