

INTER CONNECTION SCHEMATIC

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
12/26/03	A	Changed Material Specification	T.B.	B.S.	


MOUNTING INSTRUCTION:

USE 2-56 MACHINE SCREWS OR  
 EYELETS 0.089" OD BY 0.15" FLANGE  
 STIMPSON GS-3 SERIES OR EQUIVALENT  
 ALSO ADHESIVES AND DOUBLE SIDED  
 TAPES WORK WELL.

NOTES:

MATERIAL:

HOUSING: IMPACT RESISTANCE NYLON #6, BLACK, UL 94V-0,  
 MATERIAL FILE #UL E 48285  
 SPRING: SPRING STEEL, NICKLE PLATED  
 CONTACTS: SPRING STEEL, NICKLE PLATED  
 EYELETS: BRASS, NICKLE PLTD.  
 JUMPER: #24 AWG, 2.5" LONG  
 TERMINALS: BRASS, NICKLE PLTD., SNAP FASTENER  
 MALE/FEMALE TERMINALS

Tolerance (Inches)	 Memory Protection Devices, Inc. 200 Broad Hollow Road, Farmingdale, New York 11735		
Decimal		Scale	Drawn By B.S.
$\pm .5$ (.020)			Approved By T.B.
Fractional	Title		
$\pm .8$ (.030)	3AA BATTERY HOLDER WITH SNAP FASTENERS		
Angular	Date	Drawing Number	
$\pm 3^\circ$	12/26/03	BH3AA-SF	