

### **ENERGIZER 10 size - Mercury Free**






(top view) (bottom view)

# Industry Standard Dimensions

mm (inches)



## **Typical Discharge Characteristics**

ANSI/IEC Industry Standards / Intermittent Test Protocol (3K ohm 12 hours per day at 21C)



#### **Specifications**

Chemical System: Zinc Air (ZnO<sub>2</sub>)

Tab Color: Yellow

**Designation:** ANSI-7005ZD, IEC-PR70

Nominal Voltage: 1.4 Volts

Typical Capacity: 91 mAh (to 0.9 volts)


(Rated at 3k ohms at 21°C/50% RH)

**Typical Weight:** 0.32 grams (0.01 oz.)

**Typical Volume:** 0.08 cubic centimeters (0.005 cubic inch)

#### **Typical Discharge Characteristics**

IEC Industry Standards / Standard Test Protocol (3/.7 mA .1S/1H59M 59.9S 12H at 21C)



### **Typical Discharge Characteristics**

IEC Industry Standards / High Drain Test Protocol (5/1 mA .1S/1H59M 59.9S 12H at 21C)



#### **Important Notice**

This data sheet contains typical information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

Form No. EBC - 4507I Page 1 of 1