

MATERIAL:

TOP & BOTTOM \_\_\_\_\_ IMPACT RESISTANT ABS  
 FRONT & REAR PANELS \_\_\_\_\_ 0.047 THK. ALUMINUM  
 INTERNAL CHANNELS \_\_\_\_\_ 18 GA. STEEL  
 FEET \_\_\_\_\_ PLASTIC

FINISH:

TOP, BOTTOM & FEET \_\_\_\_\_ BLACK  
 FRONT & REAR PANELS \_\_\_\_\_ CLEAR ANODIZED  
 INTERNAL CHANNELS \_\_\_\_\_ ZINC PLATED

EIGHT (8) M2.5 x 4mm LG. SCREWS SUPPLIED  
 FOR ASSEMBLING PANELS TO INTERNAL CHANNELS.

FOUR (4) M3.5 x 30mm LG. SCREWS  
 SUPPLIED FOR ASSEMBLING TOP.

FOUR (4) FOOT ASSEMBLIES SUPPLIED

MOUNTING BOSSES USE EITHER M2.5 METRIC OR #4  
 STD. SHEET METAL SCREWS x 0.250" LG.  
 (NOT SUPPLIED)

NOTE: ALL DIMENSIONS HAVE  $\pm 0.015$  TOLERANCE  
 UNLESS OTHERWISE SPECIFIED

PLASTIC ENCLOSURE