



Configuration:
HD15M

| | | BNC PLUG |
|----|------------------|-------------|
| 1 | Red | 1 (Cen.) |
| 6 | Red(GND) | 1 (Shield) |
| 2 | Green | 2 (Cen.) |
| 7 | Green(GND) | 2 (Shield) |
| 3 | Blue | 3 (Cen.) |
| 8 | Blue(GND) | 3 (Shield) |
| 13 | White | 4(Cen) |
| 11 | GND(White+Black) | 4,5(Shield) |
| 14 | Black | 5(CEN) |

Material:

- 1.Cable:#28,UL2919,75 Ohm, 5COAX+Spiral,O.D.8.5
- 2.Connector: HD15M, 9th Empty, Black
BNC Plug
- 3.Thumbscrew:#4-40UNC, E32
- 4.Black Heat Shrink Tube(HD15M USE):
 - ∅ 1.5X15:4PCS
 - ∅ 3X8:3PCS
 - ∅ 5.0X8:1PC

Note:

- 1.Total Length: 2000±50mm
- 2.Color:Black
- 3.Molded Type



| | |
|---------|-------------------------------------|
| ITEM NO | AK553-2-R (2.0 M) |
| TITLE | CABLE VGA TO 5 X BNC MONITOR |

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved