



DB25 Male

**CN36 Male
(Left Angle)**

Configuration:

DB25M	CN36M
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	32
16	31
17	36
18	33
19	19
20	21
21	23
22	25
23	27
24	29
25	30
Shield	Shield

Material:

- 1. Cable: #28 25C+1+AL/MY (Beige PVC Jacket), O.D: 7.5MM
- 2. Both connectors with normal type
- 3. Thumbscrew: #4-40UNC Type
- 4. Outer Molded with Beige PVC

Note:

- 1. Total Length: 2M±5CM
- 2. Color: Beige
- 3. Molded Type



<i>ITEM NO</i>	AK525-2-R (RIGHT Angled) AK525-L-R (LEFT Angled)
<i>TITLE</i>	IEEE 1284 Printer Cable, Parallel, DSUB 25-Pin Male to CENT 36-Pin Male

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved