

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION MARCH ,2006.



© COPYRIGHT 2006 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
E	B	P	LTR	DESCRIPTION	DATE	DWN	APVD
			C	ECR-07-030288	14/12/2007	JMS	FWK

NOTES:

- ELECTRICAL DATA: CONTACT RESISTANCE: 10 mOhm MAX
INSULATION RESISTANCE: 100 MOhm MIN at 500VDC
CURRENT RATING: 5 AMPS
BREAKDOWN VOLTAGE: 500 VAC MIN PER MINUTE
- ENVIRONMENTAL: OPERATING TEMPERATURE: -20°C TO +80°C
SEALING REQUIREMENTS: IP67
- PROD SPEC: 108-3641
- PACKAGING: 107-3334
- FOR TECHNICAL DATA REFER TO YOUR LOCAL TYCO ELECTRONICS SALES OFFICE
- ALL DIMENSIONS ARE NOMINAL FOR REFERENCE ONLY UNLESS OTHERWISE STATED

ITEM	DESCRIPTION	MATERIAL	FINISH/COLOUR	QTY
1	SCREW NUT	ZINC DIE CAST	2.5µm NICKEL PLATED	1
2	CONNECTOR BODY	POLYURETHANE	BLACK	1
3	PIN CONTACT	BRASS	0.15µm GOLD OVER NICKEL	4
4	4 CORE CABLE (CORES 22AWG TO UL2464)	PVC JACKET UV RESISTANT	BLACK	1



500	40 mm	M8 STRAIGHT MALE CONNECTOR 0.5m CABLE	1-1838288-1
10000	500 mm	M8 STRAIGHT MALE CONNECTOR 10.0m CABLE	1838288-5
7000	350 mm	M8 STRAIGHT MALE CONNECTOR 7.0m CABLE	1838288-4
5000	250 mm	M8 STRAIGHT MALE CONNECTOR 5.0m CABLE	1838288-3
3000	150 mm	M8 STRAIGHT MALE CONNECTOR 3.0m CABLE	1838288-2
2000	100 mm	M8 STRAIGHT MALE CONNECTOR 2.0m CABLE	1838288-1
DIM A	TOL 'B'	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 29MAR06 MANJUNATH.T.N	Tyco Electronics Tyco Electronics Corporation Bideford, UK, EX39 4HE	
DIMENSIONS: mm		CHK 07AUG06 F.WHEELER-KING	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 07AUG06 F.WHEELER-KING	M8 STRAIGHT MALE CONNECTOR WITH STRAIN RELIEF 4 POSITION, PVC CABLE	
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		PRODUCT SPEC -	SIZE	RESTRICTED TO
MATERIAL -		APPLICATION SPEC -	CAGE CODE 00779	DRAWING NO C-1838288
FINISH -		WEIGHT -	CUSTOMER DRAWING	
		SCALE NTS		SHEET 1 OF 1 REV C