# 3M<sup>™</sup> Mini D Ribbon (MDR) Cable Assembly

.050" High Speed Video Data Transmission System, 36 Position

#### Supports LVDS Channel Link<sup>™</sup> signaling

14X36-SZ6B-XXX-0HC

- 10 shielded pairs (100 ohm) +2 drains for high bandwidth applications
- 1 USB pair & 4 singles
- High density 36 position MDR with rugged ribbon type contact
- Metal junction shell with Quick Release Latches
- EMI over-molded junction shell with rugged thumbscrew retention
- See Regulatory Information Appendix (RIA) for chemical compliance information

Date Modified: October 9, 2007

TS-2102-B Sheet 1 of 4

### **Physical**

**Connector Contact Plating** 

Wiping Area:	30 μ" [ 0.76 μm ] Min. Gold
Thumbscrew Shell Color:	Beige
Thumbscrew Shell Material:	Acrylonitrile Butadiene Styrene (ABS)
Metal shell plating:	Nickel
Metal shell material:	Aluminum, .050" [1.27 mm] Thick
Cable	
Color:	Beige
Jacket Material:	Polyvinyl Chloride (PVC)
Flammability:	AWM VW-1

### Electrical

Voltage Rating:	30 V
Current Rating:	1 A
Insulation Resistance:	$>1\times10^8\Omega$ at @100 $V_{DC}$
Withstanding Voltage:	350 $V_{RMS}$ for 1 minute
Individually Shielded Twisted Pairs	
Characteristic Impedance:	$100\pm10^{\Omega}$
<b>Conductor Size:</b>	28 AWG Stranded
<b>Propogation Velocity:</b>	1.25 ns/ft [4.1 ns/m ]

### **Environmental**

**Temperature Rating:** -20°C to +75°C

UL File No.: E86982

Channel Link is a trademark of National Semiconductor.


3M is a trademark of 3M Company. For technical, sales or ordering information call 800-225-5373

### 3M<sup>™</sup> Mini D Ribbon (MDR) Cable Assembly 14X36-SZ6B-XXX-0HC

.050" High Speed Video Data Transmission System, 36 Position

Metal Latching Shell 36 Position High Density 36 Position High Density Mini D Ribbon (MDR) Mini D Ribbon (MDR) Male Plug Male Plug 3 (⇔ Cable 10336 88 (Shielded Twisted Pairs) EM (╬ (<del>?</del>} 2X Squeeze 2X Squeeze Release Latches Release Latches 32.0 32.0 -LENGTH [1.3] [1.3] 39.8 [1.6] ⊽<u>∔</u> 19 ĥ 12.7 [0.5] MDR 36 Position Plug Both Ends mm [Inch] Assembly Length Tolerance Tolerance Unless Noted 0.0 0.00 Cable Length: Generic End Detail 0.5 to 1.5 meters -0 + .05 meters mm  $\pm .1$  $\pm .10$ MDR 36 Position Plug 2 to 10 meters -0 +3% of length (Both Ends) [] Dimensions for Reference only **Ordering Information** 14X36-SZ6B-XXX-0HC (RIA E1 & C1 apply) Backshell Options:-Length: T = Over-molded 4-40 thumbscrew 100 = 1.0 meters 1 = Metal Latching Shell 200 = 2.0 meters TS-2102-B 500 = 5.0 meters Sheet 2 of 4 3M<sup>™</sup> Mini D Ribbon (MDR) Cable Assembly 14X36-SZ6B-XXX-0HC

.050" High Speed Video Data Transmission System, 36 Position



ЗМ **Interconnect Solutions** http://www.3M.com/interconnects/

# 3M<sup>™</sup> Mini D Ribbon (MDR) Cable Assembly

.050" High Speed Video Data Transmission System, 36 Position

14X36-SZ6B-XXX-0HC

1   1   2   3   3   4   C   5	Signal       A0-       A0+       A1-       A1-       A2-       A2+       CLK1-	Position       1       19       2       20       3       21	Position       13       31       14       32       15	Signal USB Pwr Shld Gnd A4- A4+	Pair W6 Drain 6 6	Pair       1       2	Signal A0- A0+ A1-	Position       1       19       2	Position       13       31       14	Signal USB Pwr Shld Gnd A4-	Pair W6 Drain 6
1   2   3   3   4   4   5	A0+ A1- A1+ A2- A2+	19       2       20       3	31 14 32	Shld Gnd A4-	Drain 6	1 2	A0+	19	31	Shld Gnd	Drai
2 2 3 4 4 5	A1- A1+ A2- A2+	2 20 3	14 32	A4-	6	2					
2 3 3 4 4 5	A1+ A2- A2+	20 3	32				A1-	2	14	A4-	6
3 3 4 C 4 C 5	A2- A2+	3		A4+	6						0
3 4 C 4 C 5	A2+		15		0	2	A1+	20	32	A4+	6
4 C 4 C 5		21		A5-	7	3	A2-	3	15	A5-	7
4 C	CLK1-	21	33	A5+	7	3	A2+	21	33	A5+	7
5		4	16	A6-	8	4	CLK1-	4	16	A6-	8
	CLK1+	22	34	A6+	8	4	CLK1+	22	34	A6+	8
5	A3-	5	17	A7-	9	5	A3-	5	17	A7-	9
	A3+	23	35	A7+	9	5	A3+	23	35	A7+	9
	hld Gnd	6	18	CLK2-	10	Drain	Shld Gnd	6	18	CLK2-	10
	N/C	24	36	CLK2+	10		N/C	24	36	CLK2+	10
	N/C	7					N/C	7			
	N/C	25					N/C	25			
	N/C	8					N/C	8			
	N/C	26					N/C	26			
	N/C	9					N/C	9			
	DC Gnd	27				W1	DDC Gnd	27			
	DC/SCL	10				W2	DDC/SCL	10			
	DC/SDA	28				W3	DDC/SDA	28			
	DC Pwr	11				W4	DDC Pwr	11			
	SB Gnd	29				W5	USB Gnd	29			
	USB+	12				SP1	USB+	12			
SP1	USB-	30				SP2	USB-	30			
otes: All pair Pair sh	rs are indivinields are w	idually shielde	ed with aluminur inum out and in ound) is isolated	contact with si	ix internal dra ains (logic gr	ains (logic gr					

# **Regulatory Information Appendix**

**3M Electronic Solutions Division/Interconnect** 

### **EUROPE**

### Appendix E1: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

#### This product is RoHS Compliant 2005/95/EC.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

### Appendix E2: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

## This product contains lead in the compliant pin area in excess of the maximum concentration value allowed but is compliant by exemption under EU Commission Decision 2005/747/EC.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

## Appendix E3: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment as amended by Commission Decision 2005/618/EC.

#### This product contains lead in the solder tail area in excess of the maximum concentration value allowed.

Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

## Appendix E4: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

## This product contains decaBDE in the insulating material in excess of the maximum concentration value allowed but is compliant by exemption under EU Commission Decision 2005/717/EC.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

### Appendix E5: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

## This product contains lead in excess of the maximum concentration value allowed but is compliant by exemption under Item 6 of the Annex to the Directive.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

### CHINA Appendix C1: China RoHS

Electronic Industry Standard of the People's Republic of China, SJ/T11363-2006, Requirements for Concentration Limits for Certain Hazardous Substances in Electronic Information Products.

This symbol, per Marking for the Control of Pollution Caused by Electronic Information Products, SJ/T11364-2006, means that the product or part **does not** contain any of the following substances in excess of the following maximum concentration values in any homogeneous material: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

## Appendix C2: China RoHS 🝕



Electronic Industry Standard of the People's Republic of China, SJ/T11363-2006, Requirements for Concentration Limits for Certain Hazardous Substances in Electronic Information Products.

This symbol, per Marking for the Control of Pollution Caused by Electronic Information Products, SJ/T11364-2006, means that the product or part **does** contain a substance, as detailed in the chart below, in excess of the following maximum concentration values in any homogeneous material: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

The numerical reference in the symbol above should not be construed as a representation regarding the product's life or an extension of a product warranty. The product warranty is stated below. In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the product Warranty stated below.

#### 产品中有毒有害物质或元素的名称及含量 Name and Content of Hazardous Substances or Elements

部件名称	有毒有害物质或元素 (Hazardous Substances or Elements)									
(Part or Component Name)	铅(Pb)	汞 (Hg)	镉(Cd)	六价铬(Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)				
端子镀层(contact plating) × O O O O O										
hazardous substance contained in SJ/T11363-2006.) ×: 表示该有毒有害物质至少在该部件	O: 表示该有毒有害物质在该部件所有均质材料中的含量均在SJ/T11363-2006 标准规定的限量要求以下。(Indicates that this hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement in SJ/T11363-2006.) ×: 表示该有毒有害物质至少在该部件的某一均质材料中的含量超出SJ/T11363-2006 标准规定的限量要求。(Indicates that this hazardous substance contained in at least one of the homogeneous materials used for this part is above the limit									

## Appendix C3: China RoHS 4

Electronic Industry Standard of the People's Republic of China, SJ/T11363-2006, Requirements for Concentration Limits for Certain Hazardous Substances in Electronic Information Products.

This symbol, per Marking for the Control of Pollution Caused by Electronic Information Products, SJ/T11364-2006, means that the product or part **does** contain a substance, as detailed in the chart below, in excess of the following maximum concentration values in any homogeneous material: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

The numerical reference in the symbol above should not be construed as a representation regarding the product's life or an extension of a product warranty. The product warranty is stated below. In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the product Warranty stated below.

#### 产品中有毒有害物质或元素的名称及含量 Name and Content of Hazardous Substances or Elements

部件名称	有毒有害物质或元素 (Hazardous Substances or Elements)						
(Part or Component Name)	铅(Pb)	汞 (Hg)	镉 (Cd)	六价铬(Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)	
合金(Metal alloy)	×	0	0	0	0	0	

O: 表示该有毒有害物质在该部件所有均质材料中的含量均在SJ/T11363-2006 标准规定的限量要求以下。(Indicates that this hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement in SJ/T11363-2006.)

×:表示该有毒有害物质至少在该部件的某一均质材料中的含量超出SJ/T11363-2006 标准规定的限量要求。(Indicates that this hazardous substance contained in at least one of the homogeneous materials used for this part is above the limit requirement in SJ/T11363-2006.)

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



3M Electronics Interconnect Products 6801 River Place Blvd. Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3m.com/interconnects

Please recycle. Printed in USA. © 3M 2007. All rights reserved. RIA-2217B-c