



DATE BY
89/9.15

REVISION
▲

- MAT'L:
1. CABLE: #28, UL2919, 3COAX+4C+1+AL/MY+B, O.D: 8.1
 2. CONNECTOR: HD15M, 9th EMPTY, BLACK HD15F, BLACK
 3. THUMBSCREW: #4-40UNC, E32
 4. COPPER TAPE: 30 X 50
 5. BLACK HEAT SHRINK TUBE: Ø1.5x15: 6PCS Ø3x8: 6PCS

- NOTE:
1. TOTAL LENGTH: 1800±50mm
 2. COLOR: BEIGE
 3. MOLDED TYPE
 4. 360° SOLDER

CONFIGURATION:

HD15M		HD15F
1	RED (COAX.)	1
6	RED (GROUND)	6
2	GREEN (COAX.)	2
7	GREEN (GROUND)	7
3	BLUE (COAX.)	3
8	BLUE (GROUND)	8
4	BROWN	4
5	BLACK	5
13	ORANGE	13
14	WHITE	14
SHIELD	(BRAID)	SHIELD

▲ *MODIFY: BUYER NO: CC401M1-37 (AK3220 1.8M) AK3220-1.8M,
DESIGNATE INNER CORD COLOR (M00092) Y.C.C/89.9.15

④	THUMBSCREW: #4-40UNC, E32	4
③	#28, UL2919, 3COAX+4C+B, O.D: 8.1, BEIGE	1.8M
②	HD15F, BLACK	1
①	HD15M, 9th EMPTY, BLACK	1
NO.	DESCRIPTION	QTY

DATE	19 JUN, 1996	PARTS NO	MN3043N	TITLE:	HD15 MALE-HD15 FEMALE (MD TYPE)	DRAWN	S.M. 6/19	CHECK		APPRO	
UNIT	MM	DRAWN NO	001142			ASSMANN ELECTRONICS.INC					
SCALE		BUYER NO	002		AK3220 1.8M						