


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION .19
 © COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.


LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
CE	16	B	REV PER EC OB60-0048-03	21AUG03	WS JH

1. DIMENSIONS IN [] ARE IN INCHES
 △ MAXIMUM CONNECTOR LOSS IS EQUAL TO 0.50 dB PLUS CABLE ATTENUATION.



VIEW A-A
NOT TO SCALE

FIBER PATH	
LEFT CONNECTOR	RIGHT CONNECTOR
A	B
B	A



VIEW B-B
NOT TO SCALE

0.52	10.0±0.15 [393.7±6]	1-1435353-0
0.52	7.0±0.08 [275.6±3]	1435353-7
0.51	5.0±0.08 [196.9±3]	1435353-5
0.51	4.0±0.08 [157.5±3.0]	1435353-4
0.50	3.0±0.05 [118.1±2.0]	1435353-3
0.50	2.0±0.05 [78.7±2.0]	1435353-2
0.50	1.0±0.05 [39.4±2.0]	1435353-1
△ CONNECTOR LOSS (dB)	L	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN W SOURBEER 01APR03	AMP Incorporated Harrisburg, PA 17105-3608
CHK J HOFFER 01APR03	
APVD J APGAR 01APR03	
PRODUCT SPEC	
APPLICATION SPEC	NAME CABLE ASSY, FIBER OPTIC, AMPTRACS, SINGLEMODE MT-RJ TO MT-RJ, DUPLEX
MATERIAL	SIZE A2
FINISH	CAGE CODE 00779
	DRAWING NO C=1435353
	RESTRICTED TO
	CUSTOMER DRAWING
	SCALE NTS
	SHEET 1 OF 1
	REV B