


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION .19  
 © COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.


LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
CE	16	A	PER NSD05-135	13FEB2006	WS MD

1. DIMENSIONS IN [ ] ARE IN INCHES  
 2. MAXIMUM CONNECTOR LOSS IS EQUAL TO 0.50 dB PLUS CABLE ATTENUATION.



VIEW A-A  
NOT TO SCALE

FIBER PATH	
LEFT CONNECTOR	RIGHT CONNECTOR
A	B
B	A



VIEW B-B  
NOT TO SCALE

0.52	10.0±0.15 [393.7±6]	1-1499812-0
0.52	7.0±0.08 [275.6±3]	1499812-7
0.51	5.0±0.08 [196.9±3]	1499812-5
0.51	4.0±0.08 [157.5±3.0]	1499812-4
0.50	3.0±0.05 [118.1±2.0]	1499812-3
0.50	2.0±0.05 [78.7±2.0]	1499812-2
0.50	1.0±0.05 [39.4±2.0]	1499812-1
2. CONNECTOR LOSS (dB)	L	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: METERS	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN W SOURBEER 13FEB2006	CHK M DELPHIAS 13FEB2006	APVD M DELPHIAS 13FEB2006	NAME
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± -	4 PLC ± -	ANGLES ± -
MATERIAL -	FINISH -	PRODUCT SPEC -	APPLICATION SPEC -	WEIGHT -	SIZE A2
CUSTOMER DRAWING				SCALE NTS	SHEET 1 OF 1

AMP Incorporated  
Harrisburg, PA 17105-3608

CABLE ASSY, FIBER OPTIC, AMPTRACS, XG 50µm, LOF RISER, SECURE MT-RJ TO SECURE MT-RJ, DUPLEX

DRAWING NO: 1499812