



Notes:

- Cable: UL2725 80°C 30V[26AWG(1/0.404)*2F +AL/MY+Drain Wire(1/0.32*2)]TIN INS: Foam-PE OD: $\varnothing 1.1 \pm 0.05$ mm PVC Jacket OD: $\varnothing (2.2 \pm 0.1) * (7.8 \pm 0.2)$ mm Color: Red(Pantone 200C) Print: 2725 E209329 AWM 80°C 30V VW-1 Serial ATA 26AWG Lian Feng(Black Word) Impedance: 100 ± 5 OHM(Supplier: Lian Feng)
- Connector: 2-1 Material: Housing: High Temperature Polyester & Glass Fiber UL 94V-0 Terminal: Copper Alloy
2-1 Plating: Contact Area: 15u" Gold Plated
- Hood: Molded Type, PVC 45P, Color: Black(NK-K01)
- Cable Ass'y Electrical Test: 4-1: 100% Open Short & MIS Wire Test
4-2: Contact Resistance 20M OHM Min
4-3: Insulation Resistance 20M OHM Min
- Packing: See P-0039 Rev. C Packing Drawing
(Binding Size must be smaller than Blister)

DWG	P/N	L(mm)	T(mm)	EAN Code	Blister
140-0497-4	AK-SATA-030-R	300	10	4016032152712	DB VP2
140-0497-3	AK-SATA-075-R	750	20	4016032121695	DB VP2
140-0497-2	AK-SATA-100-R	1000	20	4016032121138	DB VP2
140-0497-1	AK-SATA-050-R	500	10	4016032121121	DB VP2



ITEM NO
AK-SATA-XXX-R
 TITLE Serial ATA 150 Connector Cable,
 7-Wire Cable, UL21149

ASSMANN
 Electronics, Inc.
 1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
 Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
 © Copyright 2008 by Assmann Electronic Components
 All International Rights Reserved