



- △ CONTACTS DESIGNED FOR 28 AWG STRANDED OR 26, 28, & 30 AWG SOLID WIRE.
- △ AMP TRADEMARK LOCATED IN APPROX AREA SHOWN.
- △ STANDOFFS: POS 10 (2) STANDOFFS AS SHOWN.
 14-16 (3) STANDOFFS, (1) CENTERED BETWEEN (2) SHOWN
 20-26 (4) (2)
 30 (5) (3)
 34 (6) (4)
 40-44 (7) (5)
 50 (8) (6)
 60 (9) (7)
 64 (10) (8)
- △ .000100-.000200 BRIGHT TIN LEAD, ALL OVER .000050 NICKEL.
- △ HEIGHT AFTER TERMINATION IS .253 REF.
- △ .000100-.000200 MATTE TIN, ALL OVER .000050 NICKEL.
- △ MOLDED PARTS, 94V-0 RATED THERMOPLASTIC, COLOR: BLACK. CONTACTS: PHOS BRONZE.

△6	2.100	21	2.380	2.100	2.150	43	44	2-746610-6
△6	3.100	31	3.380	3.100	3.150	63	64	2-4
△6	2.900	29	3.180	2.900	2.950	59	60	2-4
△6	1.100	11	1.380	1.100	1.150	23	24	2-3
△6	.600	6	.880	.600	.650	13	14	2-2
△6	.400	4	.680	.400	.450	9	10	2-1
△6	2.400	24	2.680	2.400	2.450	49	50	2-0
△6	1.900	19	2.180	1.900	1.950	39	40	1-9
△6	1.600	16	1.880	1.600	1.650	33	34	1-8
△6	1.400	14	1.680	1.400	1.450	29	30	1-7
△6	1.200	12	1.480	1.200	1.250	25	26	1-6
△6	.900	9	1.180	.900	.950	19	20	1-5
△6	.700	7	.980	.700	.750	15	16	1-4
△4	2.100	21	2.380	2.100	2.150	43	44	1-3
△4	3.100	31	3.380	3.100	3.150	63	64	1-2
△4	2.900	29	3.180	2.900	2.950	59	60	1-1
△4	2.400	24	2.680	2.400	2.450	49	50	1-0
△4	1.900	19	2.180	1.900	1.950	39	40	1-9
△4	1.600	16	1.880	1.600	1.650	33	34	1-8
△4	1.400	14	1.680	1.400	1.450	29	30	1-7
△4	1.200	12	1.480	1.200	1.250	25	26	1-6
△4	1.100	11	1.380	1.100	1.150	23	24	1-5
△4	.900	9	1.180	.900	.950	19	20	1-4
△4	.700	7	.980	.700	.750	15	16	1-3
△4	.600	6	.880	.600	.650	13	14	1-2
△4	.400	4	.680	.400	.450	9	10	746610-1
CONTACT FINISH	F	E	D	C	B	A	NO OF POSN	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT. DIN 11-29-86
L VARELA - DOCKS
C. ROHDE 11-29-04

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 PLC ± -
 1 PLC ± -
 2 PLC ± -
 3 PLC ± .005
 4 PLC ± -
 ANGLES ± -

MATERIAL: △ CONTACTS: SEE TABLE

APVD: M. WALMSLEY 11-29-04
 NAME: KIT, AMP-LATCH DIP PLUG, PREASSEMBLED, .100 X .100 CENTERS, FULL TIN PLATED CONTACTS

PRODUCT SPEC: 108-40013
 APPLICATION SPEC: 114-40005

SIZE: A1
 CAGE CODE: 00779
 DRAWING NO: 746610

RESTRICTED TO: -
 WEIGHT: -
 CUSTOMER DRAWING

SCALE: NTS
 SHEET: 1 OF 1
 REV: F