



MATERIALS:
 INSULATOR: P. B. T. 30%GLASS FIBER, UL94V-0
 CONTACT MATERIAL: BRASS OR PHOSPHOR BRONZE,
 UNDERPLATED: NICKEL
 CONTACT AREA: 1u²-30u² SELECTIVE GOLD
ELECTRICAL:
 CURRENT RATING: 1AMP.
 INSULATION RESISTANCE: 1000MΩMIN.
 DIELECTRIC WITHSTANDING: 500VAC
 OPERATING TEMPERATURE: -55°C-+105°C

AWLP-xx/3.2-x-R

T - TIN
 G - GOLD
 # OF CONTACTS
 (6 - 64)

	POSITION	A	B	POSITION	A	B
	6P	12.94	5.08	26P	36.40	30.48
	8P	15.48	07.62	28P	40.60	33.02
	10P	18.10	10.16	30P	43.50	35.56
	12P	20.51	12.70	34P	46.56	40.64
	14P	23.05	15.24	40P	56.20	48.26
	16P	25.64	17.78	50P	69.00	60.96
	18P	28.15	20.32	60P	81.75	73.66
	20P	30.78	22.86	64P	86.83	78.74
	24P	35.86	27.94			

UNLESS OTHERWISE SPECIFIED TOLERANCE			
±0.2			
SCALE: AS SHOWN	UNIT: mm	DRAWN NAME: TRANSITION PLUG (PITCH: 2.54 mm) 1/3 PRODUCT NO. AWLP-xx/3.2-x-R FILE NAME:	
DRAWN JOE	12/16/05		
CHECKED	/ /		
APPROVED	/ /	DATE: 12/14/05	SIZE: A4
REV. A	DESCRIPTION	DATE	REV. A



RECOMMENDED P.C.B LAYOUT
 TOLERANCES: ±0.05mm

ECN-0512100(Emily)

REV. DESCRIPTION

DATE

SIZE A4 REV. A

FILE NAME: