

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO 75 °C	STORAGE TEMPERATURE RANGE	- °C TO - °C
	VOLTAGE	5 V AC	CURRENT	1 A

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----


CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	<input type="checkbox"/>	<input type="checkbox"/>
MARKING	CONFIRMED VISUALLY.		<input type="checkbox"/>	<input type="checkbox"/>

ELECTRIC CHARACTERISTICS

INSULATION RESISTANCE	100 V DC.	100 MΩ MIN.	<input type="checkbox"/>	<input type="checkbox"/>
VOLTAGE PROOF	100 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	<input type="checkbox"/>	<input type="checkbox"/>
CONTINUITY	100 mA DC.	MUST BE CONTINUOUS.	<input type="checkbox"/>	<input type="checkbox"/>

<p>FOR REFERENCE ONLY Subject to change without notice</p>
--

REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
A CONNECTOR INDEPENDENT PERFORMANCE IS BASED ON CL240-0004-7.	<i>H. Yano</i>	<i>T. Yano</i>	<i>H. Yano</i>	<i>H. Yano</i>	
Unless otherwise specified, refer to JIS C 5402.	<i>13.8.07</i>	<i>13.8.07</i>	<i>13.8.07</i>	<i>13.8.07</i>	

Note QT:Qualification Test AT:Assurance Test O:Applicable Test

HRS HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET	PART NO. UX40-MB-5PP-500-1002
CODE NO.(OLD) CL	DRAWING NO. ELC4 - 123640	CODE NO. CL 240 - 1002 - 7
		1/1

TO
Q1



