




| PART NO. | "A" REF. APPROXIMATE OVERALL HEIGHT | "B" REF. WIRE BUNDLE |
|----------|---|-------------------------|
| TL-250 | .90 (22.9) | .20-.30 (5.1-7.6) |
| TL-350 | 1.03 (26.2) | .30-.40 (7.6-10.2) |
| TL-450 | 1.20 (30.5) | .40-.50 (10.2-12.7) |
| TL-600 | 1.33 (33.7) | .55-.65 (14.0-16.5) |
| TL-750 | 1.55 (39.4) | .70-.80 (17.8-20.3) |
| TL-950 | 1.70 (43.4) | MAX 1.00 (25.4) |
| TL-1125 | 2.19 (55.6) | MAX 1-3/16 (30.2) |
| TL-1375 | 2.68 (68.1) | MAX 1-7/16 (36.5) |
| TL-1500 | 2.93 (74.4) | MAX 1-9/16 (39.7) |
| TL-1750 | 3.45 (87.6) | MAX 1-13/16 (46.0) |

NOTES:

- MATERIAL: NYLON 6/6 (RMS-01).
FLAME RETARDANT NYLON (RMS-19)
AVAILABLE BY SPECIAL ORDER
SPECIFIED MATERIALS COMPLY WITH STANDARD SS-00259-1.
- COLOR: NATURAL.
- BLACK, RED, GREEN, & YELLOW
AVAILABLE BY SPECIAL ORDER.

| | | | | | | | | | | |
|-----|--|-------------|---|------------------|------|--|---|-------------------|---|---------------------|
| G | SEE ECN #596 FOR CHANGES | SM 03.12.03 | TITLE: TWIST-LOK | | | |   | DWG IN IN (MM) |  | |
| F | ADDED FLAME RET. NOTE- ECN #516 | SM 11.11.02 | | | | | | | | |
| E | ADDED NOTE 3 | SJ 03.13.02 | TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC=±1/64 ANG=±1' | | | | FINAL | | PART # SEE TABLE | PRINT TYPE CA |
| D | CHANGED FILE NO. AND TITLE BLOCK | SM 05.31.01 | FILE # TL | DWN: P.B. | APP: | DT: 03-22-94 DT: | | | | |
| C | RANGE OF 1125 THRU 1750 CHANGED "B" DIM TOLERANCE REMOVED | JP 8/15/94 | MAT'L: SEE NOTES | RE: RICHCO, INC. | | RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060 | | | | |
| B | P/N TL-600 AND 950 ADDED | PB 8/8/94 | | | | | | | | |
| A | P/N TL-1125/1375/1500 AND 1750 ADDED | JP 7/22/94 | | | | | | | | |
| REV | DESCRIPTION | ENGR DATE | | | | | | | | |