



## 4:1 Shrinkable Polyolefin Tubing Flexible · Dual Wall

### Smaller Sizes



**Description:** DAFLEX SM278 is a flexible, large ratio, heat shrinkable tubing with a meltable adhesive liner. When 120°C is applied, the tubing will shrink to 25% of its supplied size (4:1). Longitudinal shrinkage is 10% maximum. As the outer wall shrinks, the inner adhesive liner melts and flows. When cooled, it offers protection for a variety of electrical applications as well as "sealed-in" protection from chemicals and oils.

Because of its large shrink ratio and adhesive liner it offers excellent protection for cable repairs and retrofitting.

**Operating Temperature:** -55°C to +135°C.

Meets or exceeds MIL-I-23053/4 Class 3.

UL VW-1, CSA OFT (outer wall only).

Daburn Cat. No.	Nom. Size	Expanded ID		Recovered ID		Min. Rec. Wall		Standard Put-Up	Click to Order Prototype Quantities
		IN.	mm	IN.	mm	IN.	mm		
SM278-3/16	3/16	.157	4	.039	1	.0354	.90	200ft Spl*	<a href="#">Order</a>
SM278-5/16	5/16	.315	8	.079	2	.0354	.90	100ft Spl**	<a href="#">Order</a>
SM278-1/2	1/2	.472	12	.118	3	.0512	1.30	400ft 4ft lgths	<a href="#">Order</a>
SM278-3/4	3/4	.630	16	.157	4	.0630	1.60	200ft 4ft lgths	<a href="#">Order</a>
SM278-1"	1"	.945	24	.236	6	.0827	2.10	100ft 4ft lgths	<a href="#">Order</a>
SM278-1 1/4"	1 1/4"	1.260	32	.315	8	.0906	2.30	80ft 4ft lgths	<a href="#">Order</a>

**Standard Color:** Black. Clear and other colors are available to order.

**Standard Package:** \*1000FT, \*\*600FT. All others Standard Package shown.

To additional [Heat Shrinkable Tubing](#).

To [Heat Shrinkable Tubing Cross Reference](#) Property Chart.

Back to DABURN'S [Home Page](#).

Daburn electronics & cable corp.  
224 Pegasus Ave.  
Northvale, NJ 07647

**Tel: 201-768-5400**

**Fax: 201-768-9642**

**E-Mail: [daburn@daburn.com](mailto:daburn@daburn.com)**

**URL: <http://www.daburn.com/>**