

**WR/PG16-50M**

Order No.: 1666841

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1666841>Corrugated tube, for corrugated tube screw connection, packing  
volume 50 m, size Pg16

Commercial data	
EAN	4017918136888
Pack	1 Pcs.
Customs tariff	39173990
Weight/Piece	1.494 KG
Catalog page information	Page 466 (PC-2007)

## Product notes

WEEE/RoHS-compliant since:  
01/01/2003


<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data**

General data	
Pg screw connection	16
Material	PA
Inflammability class acc. to UL 94	HB

## Drawings

### Dimensioned drawing



### Assembly instructions for Pg16 corrugated pipe

a = Corrugated screw connection

B = Corrugated pipe

c = Opener

#### Installation note:

Cut the corrugated pipe in the groove to retain a round shape for insertion. The lighter seal (not depicted in the illustration) is positioned in the corrugated pipe screw connection below the safety latch. The darker outer seal (not depicted in the illustration) is placed over the corrugated pipe screw connection from outside. The corrugated pipe is then pushed as far as possible into the corrugated pipe screw connection and clicks into place. The screw connection is opened by placing the yellow corrugated pipe opener with force between the safety latch and the corrugated tube and the corrugated pipe is then pulled out.

**Address**

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 00  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2008 Phoenix Contact  
Technical modifications reserved;