



PANDUIT PART NO.	BUNDLE DIA.		A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	F in (mm)	G in (mm)	H in (mm)	J in (mm)	K in (mm)	MAX. PANEL THICKNESS in (mm)	MIN. LOOP TENSILE lbs (N)	CROSS SECTION	WEIGHT 100 pcs lbs (g)
	MIN. in (mm)	MAX. in (mm)														
PLWP40SD	.12 (3)	1.58 (40)	.05 (1.3)	.19 (4.8)	.46 (11.7)	.22 (5.6)	.32 (8.1)	7.0 (177.8)	.74 (18.8)	.266 (6.8)	1.3 (33)	.30 (7.6)	.118 (3.0)	50 (222)	STANDARD	.37 (168)

NOTES:

1) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE AND PART COLOR.

													DIMENSIONS IN PARENTHESIS ARE IN METRIC UNITS				
													PANDUIT CORP. TINLEY PARK, ILLINOIS				
													WINGED PUSH MOUNT CABLE TIE WITH CONVOLUTED TUBING BUMP TO PREVENT LATERAL AND AXIAL MOVEMENT PLWP40SD				
													UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± .1(2.5) (.XXX) ± .020(.51) (.XX) ± .02(.5) ANGLES ±		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.		
													DRAWN BY SO	MAT'L: HEAT STABILIZED NYLON 6.6 BLACK (-30)		SCALE	
13	10/25/04	JABO		CHANGED FORMAT FOR CONSISTENCY SEE ECN FOR DETAILS				26268	13					DATE 12-14-90	DRAWING NO. SS-26268		DWG A SIZE
REV	DATE	BY	CHK	DESCRIPTION				ECN - R	CUST	SUP				CHK'D HVP			