



PANDUIT PART NO.	BUNDLE DIA.		A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	F in (mm)	G in (mm)	H in (mm)	J in (mm)	K in (mm)	MAX. PANEL THICKNESS in (mm)	MIN. LOOP TENSILE lbs (N)	CROSS SECTION	WEIGHT 100 pcs lbs (g)
	MIN. in (mm)	MAX. in (mm)														
PLWP50SE	.12 (3)	1.97 (50)	.05 (1.3)	.19 (4.8)	.46 (11.7)	.22 (5.6)	.32 (8.1)	8.2 (208.3)	.74 (18.8)	.266 (6.8)	1.3 (33)	.30 (7.6)	.118 (3.0)	50 (222)	STANDARD	.42 (191)

NOTES:

1) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE AND PART COLOR.

										DIMENSIONS IN PARENTHESIS ARE IN METRIC UNITS								
										PANDUIT CORP. TINLEY PARK, ILLINOIS								
										WINGED PUSH MOUNT CABLE TIE WITH CONVOLUTED TUBING BUMP TO PREVENT LATERAL MOVEMENT PLWP30,50SE								
										UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ±.1(2.5) (.XXX) ±.020(.51) (.XX) ±.02(.5) ANGLES ± ---				UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.				
										DRAWN BY SO		MAT'L: HEAT STABILIZED NYLON 6.6 BLACK (-30)					SCALE NONE	
11	10/28/04	JABO	CHANGED FORMAT FOR CONSISTENCY SEE ECN FOR DETAILS						26334	11	DATE 2-11-91		DRAWING NO. SS-26334		DWG A SIZE			
REV	DATE	BY	CHK	DESCRIPTION				ECN - R	CUST	SUP	CHK'D HVP							