

Product SKU: C5770.18.01
Product Description: C5770, Coaxial Cable, RG59/U Type, 22 AWG Solid Copper Clad Steel, 100% Flexfoil® Bonded +40% Aluminum Braid, PVC Jacket - Black - 500 Ft. Spool
Product Category: Electronics - Coaxial Cable - RG 59/U - Black

**Product Construction:**

- | | |
|------------------|---|
| Conductor: | <ul style="list-style-type: none">• Copper clad steel per ASTM B-869 |
| Insulation/Core: | <ul style="list-style-type: none">• Cellular polyethylene design |
| Shield: | <ul style="list-style-type: none">• Aluminum braid• Flexfoil® shield |
| Jacket: | <ul style="list-style-type: none">• Premium PVC compound |

Product Specification:

- | | |
|-------------------------------------|--|
| No. of Conductors: | <ul style="list-style-type: none">• 1 |
| Conductor Size (AWG): | <ul style="list-style-type: none">• 22 |
| Jacket Color: | <ul style="list-style-type: none">• Black |
| Insulation Material (in): | <ul style="list-style-type: none">• Cellular Polyethylene 0.144 |
| Insulation Material (mm): | <ul style="list-style-type: none">• Cellular Polyethylene 3.66 |
| Shield Coverage Nominal Shield DCR: | <ul style="list-style-type: none">• 100% Flexfoil® Bonded +40% Aluminum Braid 11.0 Ohm/M |
| Nominal Outside Diameter (in): | <ul style="list-style-type: none">• 0.231 |
| Nominal Outside Diameter (mm): | <ul style="list-style-type: none">• 5.87 |

Nominal Capacitance (pF/ft):	• 16.00
Nominal Capacitance (pF/m):	• 52.50
Velocity of Propagation %:	• 78
Nominal Impedance Ohm:	• 80
Nominal Attenuation MHz/dB per 100 ft:	• 1000/9.40
	• 50/2.30
	• 100/3.30
	• 200/4.10
	• 1/0.50
	• 10/1.00
	• 500/6.50
Standard Packaging:	• 500' Spool
Standard Package Quantity:	• 1
UPC #:	• 079407740017
Put-up:	• 500
SCC-14:	• 50079407740011
Cube:	• 847.44
Weight Per Unit of Measure:	• .02
ColorOption:	• Black

Product Information:

Applications:

- CATV
- Citizen band radio
- Drop cable
- Local Area Network (LAN)
- MATV
- Monitor/VDT Display
- Suitable for RF signal transmission

Compliances:

- NEC CL2, CATV, CM, CEC CM
- NEC/CEC Type CMG (CSA: 80°C, 300V)

Packaging:

- 1000 foot (305 m) Pull-Pac ® Cartons
- 1000' (305 m) Reels
- 500' (152 m) Spools
- Other put-ups available- consult Customer Service

Technical Specifications

[4' Electrical Wire Center](#)

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)



**CAROL
BRAND**