This information is confidential and is disclosed to you on condition that no further disclosure is made by you to other than T & B Personnel without written authorization from
THOMAS & BETTS INTERNATIONAL

NUMBER A2

T&B

FLEXSTRIP* JUMPERS

2/86

†CONDUCTOR PITCH "A"		MARGIN C (min.)		THICKNESS D (MAX.)		PIN DIAMETER E ±0,025 (±.001")		NUMBER OF CONDUCTORS	
Cat.Ref.	mm (inch)	mm	(inch.)	mm	(inch.)	mm	(inch.)	min.	max.
1	1,27 .050"	0,25	.010"	0,64	.025"	0,320	.0126"	2	30
6	1,90 .075"	0,38	.015"	0,84	.033"	0,404	.0159"	2	30
2	2,54 .100"	0,51	.020"	0,84	.033"	0,511	.0201"	2	30
3	3,18 .125"	1,52	.060"	0,84	.033"	0,511	.0201"	2	25
4	3,81 .150"	1,52	.060"	0,84	.033"	0,511	.0201"	2	20
5	5,08 .200"	1,52	.060"	0,84	.033"	0,511	.0201"	2	15



Dimensions are shown in mm (inches.)
† Tolerance on Pitch ±0,25 (0.01") non-cumulative.

INSULATION LENGTH B ±1.57 (±0.062")		
mm	(inch)	Cat. Ref.
25.4	1	1
38.1	1½	1.5
50.8	2	2
63.5	2½	2.5
76.2	3	3
88.9	3½	3.5
101.6	4	4
114.3	4½	4.5
127	5	5
139.7	5½	5.5
152.4	6	6

PROPERTIES :-
Insulation Material - Nomex#
Temperature Rating - 105°C
Current Rating - 2 amps
U.L. Style Number - 5188

NOTES:-
* Trademark of Thomas & Betts Corporation
# Registered trademark of E.I. Du Pont de Nemours

CATALOGUE NUMBERING SYSTEM

FSN-XXA-X

- FSN — Product Code
- XX — Conductor Pitch (see table for ref' N°)
- A — Insulation Length (see table for ref' N°)
- X — Straight Pin
- X — Number of Conductors (see table for max' number)

EXAMPLE:-

FSN -22A - 15

FSN - Flexstrip Jumper With Nomex Insulation
2 - Conductor Pitch 2.54 (0.100)
2 - Insulation Length 50.8 (2)
A - Straight Pin
15 - Number of Conductors 15

T&B THOMAS & BETTS INTERNATIONAL
EUROPEAN ENGINEERING DIVISION

DRG. N°
3S-10018

IMPERIAL DIMENSIONS SHOWN THUS [ ]
TOLERANCES
·0000 EQUALS ± ·0002
·000 EQUALS ± ·003
·00 EQUALS ± ·015

THIRD ANGLE PROJECTION

REV	DESCRIPTION	DATE	BY
0			

MATERIAL | PART NAME
HEAT TREAT | PRODUCT CODE
FINISH | TOLERANCES UNLESS OTHERWISE SPECIFIED
SCALE
DR.
CH.
APP.

FSN-11.5A-12.
=

tyco Electronics 1437129-7 Rev 0 SHT 1 OF 1