

Product SKU: C1320.21.03
Product Description: Hook-Up Wire, PVC Test Lead, No. of Conductors: 1, Gauge Size (AWG): 18, Conductor/Strands: 65/36, Temperature Range: -25Â°C to +60Â°C - Red - 1000 Ft. Spool
Product Category: Electronics - Hook-Up Wire - Rubber/PVC Test Lead - PVC Test Lead - Red

**Product Construction:**

- Conductor:
- Fully-annealed, stranded tinned copper per ASTM B-33
- Insulation:
- Temperature range: -25Â°C to +60Â°C PVC
 - Premium grade color coded Polyvinylchloride (PVC)

Product Specification:

- No. of Conductors:
- 1
- Conductor Size (AWG):
- 18
- Conductor/Strands:
- 65/36
- Jacket Color:
- Red
- Nominal Insulation Thickness (in):
- 0.045
- Nominal Insulation Thickness (mm):
- 1.14
- Breakdown Voltage (AC,ms):
- 20,000V
- Working Voltage:
- 5,000V
- Nominal Outside Diameter (in):
- 0.140
- Nominal Outside Diameter (mm):
- 3.56
- Standard Packaging:
- 1000' Spool

Standard Package Quantity:	• 1
UPC #:	• 079407815135
Footnote:	• For intermittent duty only.
Put-up:	• 1000
SCC-14:	• 50079407815133
Cube:	• 528.471
Weight Per Unit of Measure:	• .01
ColorOption:	• Red

Product Information:

Applications:	<ul style="list-style-type: none"> • Oscillators • Test equipment
Packaging:	<ul style="list-style-type: none"> • 1000' (305 m) Spools • 500' (152m) Reels • 5000' (1524m) Reels • Other put-ups available- consult Customer Service

Reference Charts

[Color Code Chart](#)

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)

**CAROL
BRAND**