

**Product SKU:** C2003.21.05

**Product Description:** Hook-Up Wire, UL 1007, UL 1569, CSA TR-64, Gauge Size (AWG): 24, Conductor/Strands: Solid,

Jacket: Premium Grade PVC, Temperature Range: -20°C to +105°C - Yellow - 1000 Ft. Spool

**Product Category:** Electronics - Hook-Up Wire - UL 1007, UL 1569, CSA TR-64 - SOLID CONDUCTORS - Yellow



## **Product Construction:**

Conductor: • 24 thru 16 AWG

• Fully-annealed, tinned copper per ASTM B-33

Solid or stranded

Insulation: • Color Code: See chart below

• Premium grade color-coded PVC

• Temperature range:  $-20\hat{A}^{\circ}C$  to  $+105\hat{A}^{\circ}C$ 

## **Product Specification:**

Conductor Size (AWG): • 24

Conductor/Strands: • Solid

No. of Pairs: • 1

Jacket Color: • Yellow

Nominal Insulation Thickness

(in):

• 0.016

Nominal Insulation Thickness

(mm):

• 0.40

Nominal Outside Diameter (in): • 0.052

Nominal Outside Diameter

(mm):

• 1.32

Standard Packaging: • 1000' Spool

Standard Package Quantity:	• 1
UPC #:	• 079407765058
Put-up:	• 1000
SCC-14:	• 50079407765055
Cube:	• 164.58986
Weight Per Unit of Measure:	• .0024
ColorOption:	• Yellow
Product Information:	
Applications:	• Internal wiring of electrical and electronic equipment
	• Internal wiring of panels and meters
	Point-to-point wiring
	• Suggested voltage rating: 300 Volts
Compliances:	• CSA TR-64 - 90°C, 300V
	• Designed to Meet UL VW-1 Vertical Wire Flame Test
	• UL Style 1007 - 80°C, 300V
	• UL Style 1569 - 105°C, 300V
Packaging:	• 10,000 foot (3048m) Reels
	• 1000' (305m) Spools
	Other put-ups available- consult Customer Service
Reference Charts Color Code Chart	
Technical Specifications	
Unit Conversion Factors	
Cable Design Equations - Balanced Pair	
Insulation and Jacket Properties	

**Temperature Conversion Chart** 

<u>Decimal and Unit Conversion Factors</u> <u>Cable Design Equations - Braid Shield</u> AWG Conductor Chart
Conduit Capacity Chart
Cable Design Equations

Cable Design Equations - Coaxial Cable

**Engineering Prefixes** 

Coax Connector Cross Reference

Glossary





Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

