

Product SKU: C2004.21.04

Product Description: Hook-Up Wire, UL 1007, UL 1569, CSA TR-64, Gauge Size (AWG): 22, Conductor/Strands: Solid,

Jacket: Premium Grade PVC, Temperature Range: -20°C to +105°C - Orange - 1000 Ft. Spool

Product Category: Electronics - Hook-Up Wire - UL 1007, UL 1569, CSA TR-64 - SOLID CONDUCTORS - Orange



Product Construction:

Conductor: • 24 thru 16 AWG

• Fully-annealed, tinned copper per ASTM B-33

• Solid or stranded

Insulation: • Color Code: See chart below

• Premium grade color-coded PVC

• Temperature range: $-20\hat{A}^{\circ}C$ to $+105\hat{A}^{\circ}C$

Product Specification:

Conductor Size (AWG): • 22

Conductor/Strands: • Solid

No. of Pairs: • 1

Jacket Color: • Orange

Nominal Insulation Thickness

(in):

• 0.016

Nominal Insulation Thickness

(mm):

• 0.40

Nominal Outside Diameter (in): • 0.057

Nominal Outside Diameter

(mm):

• 1.45

Standard Packaging: • 1000' Spool

| Standard Package Quantity: | • 1 |
|---|--|
| UPC #: | • 079407765324 |
| Put-up: | • 1000 |
| SCC-14: | • 50079407765322 |
| Cube: | • 216.72 |
| Weight Per Unit of Measure: | • .0036 |
| ColorOption: | • Red |
| Product Information: | |
| Applications: | • Internal wiring of electrical and electronic equipment |
| | • Internal wiring of panels and meters |
| | Point-to-point wiring |
| | • Suggested voltage rating: 300 Volts |
| Compliances: | • CSA TR-64 - 90°C, 300V |
| | • Designed to Meet UL VW-1 Vertical Wire Flame Test |
| | • UL Style 1007 - 80°C, 300V |
| | • UL Style 1569 - 105°C, 300V |
| Packaging: | • 10,000 foot (3048m) Reels |
| | • 1000' (305m) Spools |
| | Other put-ups available- consult Customer Service |
| Reference Charts | |
| Color Code Chart | |
| Technical Specifications <u>Unit Conversion Factors</u> <u>Cable Design Equations - Balanced Pair</u> | |

T

U \mathbf{C} **Insulation and Jacket Properties Temperature Conversion Chart Decimal and Unit Conversion Factors** Cable Design Equations - Braid Shield AWG Conductor Chart
Conduit Capacity Chart
Cable Design Equations

Cable Design Equations - Coaxial Cable

Engineering Prefixes

Coax Connector Cross Reference

Glossary





Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

