

Product SKU: C2016.12.03
Product Description: Hook-Up Wire, UL 1007, UL 1569, CSA TR-64, Gauge Size (AWG): 22, Conductor/Strands: 7/30, Jacket: Premium Grade PVC, Temperature Range: -20Â°C to +105Â°C - Red - 100 Ft. Spool
Product Category: Electronics - Hook-Up Wire - UL 1007, UL 1569, CSA TR-64 - STRANDED CONDUCTORS - Red

**Product Construction:**

- Conductor:**
- 24 thru 16 AWG
 - Fully-annealed, tinned copper per ASTM B-33
 - Solid or stranded
- Insulation:**
- Color Code: See chart below
 - Premium grade color-coded PVC
 - Temperature range: -20Â°C to +105Â°C

Product Specification:

- Conductor Size (AWG):** • 22
- Conductor/Strands:** • 7/30
- No. of Pairs:** • 1
- Jacket Color:** • Red
- Nominal Insulation Thickness (in):** • 0.016
- Nominal Insulation Thickness (mm):** • 0.40
- Nominal Outside Diameter (in):** • 0.062
- Nominal Outside Diameter (mm):** • 1.57
- Standard Packaging:** • 100' Spool

Standard Package Quantity:	<ul style="list-style-type: none"> • 4
UPC #:	<ul style="list-style-type: none"> • 079407002504
Put-up:	<ul style="list-style-type: none"> • 100
Cube:	<ul style="list-style-type: none"> • 164.58986
Weight Per Unit of Measure:	<ul style="list-style-type: none"> • .0038
ColorOption:	<ul style="list-style-type: none"> • Red

Product Information:

Applications:	<ul style="list-style-type: none"> • Internal wiring of electrical and electronic equipment • Internal wiring of panels and meters • Point-to-point wiring • Suggested voltage rating: 300 Volts
Compliances:	<ul style="list-style-type: none"> • CSA TR-64 - 90Â°C, 300V • Designed to Meet UL VW-1 Vertical Wire Flame Test • UL Style 1007 - 80Â°C, 300V • UL Style 1569 - 105Â°C, 300V
Packaging:	<ul style="list-style-type: none"> • 10,000 foot (3048m) Reels • 1000' (305m) Spools • Other put-ups available- consult Customer Service

Reference Charts

[Color Code Chart](#)

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

