

<b>Product SKU:</b>	C2101.21.04
	Hook-Up Wire, UL 1015, CSA TEW, Gauge Size (AWG): 22, Conductor/Strands: 7/30, Jacket: Premium Grade PVC, Temperature Range: -20°C to +105°C - Orange - 1000 Ft. Spool
Product Category:	Electronics - Hook-Up Wire - UL 1015, CSA TEW - STRANDED CONDUCTORS - Orange



## **Product Construction:**

Conductor:	• 24 thru 10 AWG	
	• Fully-annealed, tinned copper per ASTM B-33	
	• Solid or stranded	
Insulation:	• Color Code: See chart below	
	• Premium grade color-coded PVC	
	• Temperature range: $-20\hat{A}^{\circ}C$ to $+105\hat{A}^{\circ}C$	
Product Specification:		
Conductor Size (AWG):	• 22	
Conductor/Strands:	• 7/30	
No. of Pairs:	• 1	
Jacket Color:	• Orange	
Nominal Insulation Thickness (in):	• 0.032	
Nominal Insulation Thickness (mm):	• 0.81	
Nominal Outside Diameter (in):	• 0.094	
Nominal Outside Diameter (mm):	• 2.38	

Standard Packaging: • 1000' Spool

Standard Package Quantity:	• 1
UPC #:	• 079407767878
Put-up:	• 1000
SCC-14:	• 50079407767877
Cube:	• 328.44
Weight Per Unit of Measure:	• .01
ColorOption:	• Red
Product Information:	
Applications:	• Internal wiring of electrical and electronic equipment
	• Internal wiring of panels and meters
	• Point-to-point wiring
	• Suggested voltage rating: 600 Volts
Compliances:	• CSA Type TEW
	• Designed to Meet UL VW-1 Vertical Wire Flame Test
	• UL Style 1015 - 105°C, 600V
Packaging:	• 10,000 foot (3048m) Reels
	• 1000' (305 m) Spools
	• Other put-ups available- consult Customer Service
Reference Charts	
Color Code Chart	
Technical Specifications	

Unit Conversion Factors Cable Design Equations - Balanced Pair Insulation and Jacket Properties Temperature Conversion Chart Decimal and Unit Conversion Factors Cable Design Equations - Braid Shield AWG Conductor Chart Conduit Capacity Chart Cable Design Equations - Coaxial Cable Engineering Prefixes Coax Connector Cross Reference Glossary





Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

