

**Product SKU:** C2107.41.05

**Product Description:** Hook-Up Wire, UL 1015, CSA TEW, Gauge Size (AWG): 10, Conductor/Strands: 105/30, Jacket:

Premium Grade PVC, Temperature Range: -20°C to +105°C - Yellow - 1000 Ft. Reel

**Product Category:** Electronics - Hook-Up Wire - UL 1015, CSA TEW - STRANDED CONDUCTORS - Yellow



## **Product Construction:**

Conductor: • 24 thru 10 AWG

• Fully-annealed, tinned copper per ASTM B-33

• Solid or stranded

Insulation: • Color Code: See chart below

• Premium grade color-coded PVC

• Temperature range:  $-20\hat{A}^{\circ}C$  to  $+105\hat{A}^{\circ}C$ 

## **Product Specification:**

Conductor Size (AWG): • 10

Conductor/Strands: • 105/30

No. of Pairs: • 1

Jacket Color: • Yellow

Nominal Insulation Thickness

(in):

• 0.032

Nominal Insulation Thickness

(mm):

• 0.81

Nominal Outside Diameter (in): • 0.184

Nominal Outside Diameter

(mm):

4.67

Standard Packaging: •

• 1000' Non-returnable Wood Reels

Standard Package Quantity:	• 1
UPC #:	• 079407769230
Put-up:	• 1000
SCC-14:	• 50079407769233
Cube:	• 2548
Weight Per Unit of Measure:	• .0412
ColorOption:	• Yellow
Product Information:	
Applications:	Internal wiring of electrical and electronic equipment
	<ul> <li>Internal wiring of panels and meters</li> </ul>
	Point-to-point wiring
	• Suggested voltage rating: 600 Volts
Compliances:	• CSA Type TEW
	Designed to Meet UL VW-1 Vertical Wire Flame Test
	• UL Style 1015 - 105°C, 600V
Packaging:	• 10,000 foot (3048m) Reels
	• 1000' (305 m) Spools
	Other put-ups available- consult Customer Service
Reference Charts Color Code Chart	
<b>Technical Specifications</b>	
Unit Conversion Factors	
Cable Design Equations - Balanced Pair	
Insulation and Jacket Properties	
Temperature Conversion Chart	
Decimal and Unit Conversion Factors	
Cable Design Equations - Braid Shield	
AWG Conductor Chart Conduit Capacity Chart	
Conduit Cupacity Chart	

<u>Cable Design Equations - Coaxial Cable</u> <u>Engineering Prefixes</u> <u>Coax Connector Cross Reference</u>



Glossary



Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

