

Product SKU:	C2117.21.05
Product Description:	Hook-Up Wire, UL 1015, CSA T Premium Grade PVC, Temperatu
Product Category:	Electronics - Hook-Up Wire - UL

Hook-Up Wire, UL 1015, CSA TEW, Gauge Size (AWG): 22, Conductor/Strands: Solid, Jacket: Premium Grade PVC, Temperature Range: -20°C to +105°C - Yellow - 1000 Ft. Spool Electronics - Hook-Up Wire - UL 1015, CSA TEW - SOLID CONDUCTORS - Yellow



## **Product Construction:**

Conductor:

- 24 thru 10 AWG
- Fully-annealed, tinned copper per ASTM B-33
- Solid or stranded

Insulation:

- Color Code: See chart below
- Premium grade color-coded PVC
- Temperature range:  $-20\hat{A}^{\circ}C$  to  $+105\hat{A}^{\circ}C$

## **Product Specification:**

Conductor Size (AWG):	• 22
Conductor/Strands:	• Solid
No. of Pairs:	• 1
Jacket Color:	• Yellow
Nominal Insulation Thickness (in):	• 0.032
Nominal Insulation Thickness (mm):	• 0.81
Nominal Outside Diameter (in):	• 0.089
Nominal Outside Diameter (mm):	• 2.26
Standard Packaging:	• 1000' Spool

UPC #:       • 079407769346         Put-up:       • 1000         SCC-14:       • 50079407769344         Cube:       • 5144.832         Weight Per Unit of Measure:       • .01         ColorOption:       • Yellow         Product Information:       • Yellow         Applications:       • Internal wiring of electrical and electronic equipment         • Foint-to-point wiring       • Suggested voltage rating: 600 Volts         Compliances:       • CSA Type TEW         • Designed to Meet UL VW-1 Vertical Wire Flame Test       • UL Style 1015 - 105ŰC, 600V         Packaging:       • 10,000 foot (3048m) Reels         • 10000' (305 m) Spools       • Other put-ups available- consult Customer Service	Standard Package Quantity:	• 1
SCC-14:• 50079407769344Cube:• 5144.832Weight Per Unit of Measure:• .01ColorOption:• YellowProduct Information:• YellowApplications:• Internal wiring of electrical and electronic equipment • Internal wiring of panels and meters • Point-to-point wiring • Suggested voltage rating: 600 VoltsCompliances:• CSA Type TEW • Designed to Meet UL VW-1 Vertical Wire Flame Test • UL Style 1015 - 105ŰC, 600VPackaging:• 10,000 foot (3048m) Reels • 1000' (305 m) Spools • Other put-ups available- consult Customer ServiceReference Charts Color Code Chart• UL Style Internation Service	UPC #:	• 079407769346
Cube:• 5144.832Weight Per Unit of Measure:• .01ColorOption:• YellowProduct Information:• Internal wiring of electrical and electronic equipment • Internal wiring of panels and meters • Point-to-point wiring • Suggested voltage rating: 600 VoltsCompliances:• CSA Type TEW • Designed to Meet UL VW-1 Vertical Wire Flame Test • IUL Style 1015 - 105ŰC, 600VPackaging:• 10,000 foot (3048m) Reels • 1000' (305 m) Spools • Other put-ups available- consult Customer ServiceKervence Charts Compliances:• Other put-ups available- consult Customer Service	Put-up:	• 1000
Weight Per Unit of Measure:• .01ColorOption:• YellowProduct Information:• Internal wiring of electrical and electronic equipment • Internal wiring of panels and meters • Point-to-point wiring • Suggested voltage rating: 600 VoltsCompliances:• CSA Type TEW • Designed to Meet UL VW-1 Vertical Wire Flame Test • UL Style 1015 - 105ŰC, 600VPackaging:• 10,000 foot (3048m) Reels • 1000' (305 m) Spools • Other put-ups available- consult Customer ServiceReference Charts Color Code Chart• UL Style Internation Spools • Other put-ups available- consult Customer Service	SCC-14:	• 50079407769344
ColorOption:• YellowProduct Information:• Internal wiring of electrical and electronic equipment • Internal wiring of panels and meters • Point-to-point wiring • Suggested voltage rating: 600 VoltsCompliances:• CSA Type TEW • Designed to Meet UL VW-1 Vertical Wire Flame Test • UL Style 1015 - 105ŰC, 600VPackaging:• 10,000 foot (3048m) Reels • 1000° (305 m) Spools • Other put-ups available- consult Customer ServiceReference Charts Color Code Chart• Yellow	Cube:	• 5144.832
Product Information: <ul> <li>Applications:</li> <li>Internal wiring of electrical and electronic equipment</li> <li>Internal wiring of panels and meters</li> <li>Point-to-point wiring</li> <li>Suggested voltage rating: 600 Volts</li> <li>Compliances:</li> <li>CSA Type TEW</li> <li>Designed to Meet UL VW-1 Vertical Wire Flame Test</li> <li>UL Style 1015 - 105ŰC, 600V</li> <li>Packaging:</li> <li>10,000 foot (3048m) Reels</li> <li>1000' (305 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul> Reference Charts	Weight Per Unit of Measure:	• .01
Applications:• Internal wiring of electrical and electronic equipment• Internal wiring of panels and meters• Point-to-point wiring• Suggested voltage rating: 600 VoltsCompliances:• CSA Type TEW• Designed to Meet UL VW-1 Vertical Wire Flame Test• UL Style 1015 - 105ŰC, 600VPackaging:• 10,000 foot (3048m) Reels• 1000' (305 m) Spools• Other put-ups available- consult Customer ServiceReference Charts	ColorOption:	• Yellow
<ul> <li>Internal wiring of panels and meters</li> <li>Point-to-point wiring</li> <li>Suggested voltage rating: 600 Volts</li> <li>Compliances:</li> <li>CSA Type TEW</li> <li>Designed to Meet UL VW-1 Vertical Wire Flame Test</li> <li>UL Style 1015 - 105ŰC, 600V</li> <li>Packaging:</li> <li>10,000 foot (3048m) Reels</li> <li>1000' (305 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul>	Product Information:	
<ul> <li>Point-to-point wiring</li> <li>Suggested voltage rating: 600 Volts</li> <li>Compliances:         <ul> <li>CSA Type TEW</li> <li>Designed to Meet UL VW-1 Vertical Wire Flame Test</li> <li>UL Style 1015 - 105ŰC, 600V</li> </ul> </li> <li>Packaging:         <ul> <li>10,000 foot (3048m) Reels</li> <li>1000' (305 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul> </li> </ul>	Applications:	• Internal wiring of electrical and electronic equipment
<ul> <li>Suggested voltage rating: 600 Volts</li> <li>Compliances:</li> <li>CSA Type TEW         <ul> <li>Designed to Meet UL VW-1 Vertical Wire Flame Test</li> <li>UL Style 1015 - 105ŰC, 600V</li> </ul> </li> <li>Packaging:         <ul> <li>10,000 foot (3048m) Reels</li> <li>1000' (305 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul> </li> </ul>		• Internal wiring of panels and meters
Compliances: <ul> <li>CSA Type TEW</li> <li>Designed to Meet UL VW-1 Vertical Wire Flame Test</li> <li>UL Style 1015 - 105ŰC, 600V</li> </ul> Packaging: <ul> <li>10,000 foot (3048m) Reels</li> <li>1000' (305 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul> Reference Charts Color Code Chart		• Point-to-point wiring
<ul> <li>Designed to Meet UL VW-1 Vertical Wire Flame Test</li> <li>UL Style 1015 - 105°C, 600V</li> <li>Packaging:</li> <li>10,000 foot (3048m) Reels</li> <li>1000' (305 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul> Reference Charts Color Code Chart		• Suggested voltage rating: 600 Volts
<ul> <li>UL Style 1015 - 105°C, 600V</li> <li>Packaging:</li> <li>10,000 foot (3048m) Reels</li> <li>1000' (305 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul> Reference Charts Color Code Chart	Compliances:	• CSA Type TEW
<ul> <li>Packaging:</li> <li>10,000 foot (3048m) Reels</li> <li>1000' (305 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul> Reference Charts Color Code Chart		• Designed to Meet UL VW-1 Vertical Wire Flame Test
<ul> <li>1000' (305 m) Spools</li> <li>Other put-ups available- consult Customer Service</li> </ul> Reference Charts Color Code Chart		• UL Style 1015 - 105°C, 600V
Other put-ups available- consult Customer Service     Reference Charts     Color Code Chart	Packaging:	• 10,000 foot (3048m) Reels
Reference Charts Color Code Chart		• 1000' (305 m) Spools
Color Code Chart		• Other put-ups available- consult Customer Service
	Reference Charts	
Tachnical Specifications	Color Code Chart	
recumcar specifications	Technical Specifications	

<u>Unit Conversion Factors</u> <u>Cable Design Equations - Balanced Pair</u> <u>Insulation and Jacket Properties</u> <u>Temperature Conversion Chart</u> <u>Decimal and Unit Conversion Factors</u> <u>Cable Design Equations - Braid Shield</u> <u>AWG Conductor Chart</u> <u>Conduit Capacity Chart</u> Cable Design Equations - Coaxial Cable Engineering Prefixes Coax Connector Cross Reference Glossary





Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

