

**Product SKU:** C1356.21.01

**Product Description:** Speaker Wire, UL Listed (Wires, Misc.) 120V max., No. of Conductors: 2, Gauge Size (AWG): 24,

Conductor/Strands: 7/32, Jacket: Premium Grade PVC - Black - 1000 Ft. Spool

**Product Category:** Electronics - Special Applications - Audio, Video, and Entertainment Cable - Speaker Wire - Black



## **Product Construction:**

Conductor: • 24 thru 12 AWG fully-annealed 1 bare, 1 tin stranded copper per ASTM B-174

Insulation/Jacket: • Premium grade PVC

**Product Specification:** 

No. of Conductors: 2

Conductor Size (AWG): 24

Conductor/Strands: • 7/32

Jacket Color: Black

Nominal Insulation Thickness (in):

• 0.016

Nominal Insulation Thickness

(mm):

• 0.41

Nominal Outside Diameter (in): • 0.055 x 0.110

Nominal Outside Diameter

(mm):

• 1.39 x 2.79

Standard Packaging: 1000' Spool

Standard Package Quantity: 2

UPC #: 079407762057

Put-up:	• 1000
SCC-14:	• 50079407762055
Cube:	• 499.686
Weight Per Unit of Measure:	• .01
ColorOption:	• Black
<b>Product Information:</b>	
Applications:	Hi-fi and stereo speaker wire
	• Juke boxes
	• Lamps
	• Radios
	• Suggested voltage rating: 120 Volts
	• Not for in-wall use
Compliances:	• UL Wires Misc. (UL: 120V)
Packaging:	• 1000' (305 m) Spools
	• 500' (152 m) Spools
	Other put-ups available- consult Customer Service
<b>Technical Specifications</b>	
<u>Unit Conversion Factors</u>	
Cable Design Equations - Balanced Pair	
<u>Insulation and Jacket Properties</u> <u>Temperature Conversion Chart</u>	
Decimal and Unit Conversion Factors	
Cable Design Equations - Braid Shield	
AWG Conductor Chart	
Conduit Capacity Chart	
Cable Design Equations - Coaxial Cable	
<b>Engineering Prefixes</b>	
Coax Connector Cross Reference	
Glossary	



## CAROL BRAND