

**Product SKU:** C1358.21.90  
**Product Description:** Speaker Wire, UL Listed (Wires, Misc.) 120V max., No. of Conductors: 2, Gauge Size (AWG): 16, Conductor/Strands: 26/30, Jacket: Premium Grade PVC - Clear - 1000 Ft. Spool  
**Product Category:** Electronics - Special Applications - Audio, Video, and Entertainment Cable - Speaker Wire - Clear



**Product Construction:**

- Conductor:
- 24 thru 12 AWG fully-annealed 1 bare, 1 tin stranded copper per ASTM B-174
- Insulation/Jacket:
- Premium grade PVC

**Product Specification:**

- No. of Conductors:
- 2
- Conductor Size (AWG):
- 16
- Conductor/Strands:
- 26/30
- Jacket Color:
- Clear
- Nominal Insulation Thickness (in):
- 0.025
- Nominal Insulation Thickness (mm):
- 0.64
- Nominal Outside Diameter (in):
- 0.112 x 0.224
- Nominal Outside Diameter (mm):
- 2.84 x 5.33
- Standard Packaging:
- 1000' Spool
- Standard Package Quantity:
- 1
- UPC #:
- 079407762309

- Put-up: • 1000
- SCC-14: • 50079407762300
- Cube: • 824.04
- Weight Per Unit of Measure: • .03
- ColorOption: • Clear

### **Product Information:**

- Applications:
- Hi-fi and stereo speaker wire
  - Juke boxes
  - Lamps
  - Radios
  - Suggested voltage rating: 120 Volts
  - Not for in-wall use
- Compliances:
- UL Wires Misc. (UL: 120V)
- Packaging:
- 1000' (305 m) Spools
  - 500' (152 m) Spools
  - Other put-ups available- consult Customer Service

### **Technical Specifications**

[4' Carol Brand Electrical Wire Center](#)

[3' Carol Brand Electrical Wire Center](#)

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)



**CAROL  
BRAND**