

**Product SKU:** C1358.18.90

**Product Description:** Speaker Wire, UL Listed (Wires, Misc.) 120V max., No. of Conductors: 2, Gauge Size (AWG): 16,

Conductor/Strands: 26/30, Jacket: Premium Grade PVC - Clear - 500 Ft. Spool

Product Category: Electronics - Special Applications - Audio, Video, and Entertainment Cable - Speaker Wire - Clear



## **Product Construction:**

Conductor: • 24 thru 12 AWG fully-annealed 1 bare, 1 tin stranded copper per ASTM B-174

Insulation/Jacket: • Premium grade PVC

**Product Specification:** 

No. of Conductors: • 2

Conductor Size (AWG): • 16

Conductor/Strands: • 26/30

Jacket Color: • Clear

Nominal Insulation Thickness

(in):

• 0.025

Nominal Insulation Thickness

(mm):

0.64

Nominal Outside Diameter (in): • 0.112 x 0.224

Nominal Outside Diameter

(mm):

• 2.84 x 5.33

Standard Packaging: • 500' Spool

Standard Package Quantity: • 2

UPC #: • 079407762255

Put-up:	• 500
SCC-14:	• 50079407762255
Cube:	• 891.1
Weight Per Unit of Measure:	• .03
ColorOption:	• Clear
<b>Product Information:</b>	
Applications:	Hi-fi and stereo speaker wire
	• Juke boxes
	• Lamps
	• Radios
	• Suggested voltage rating: 120 Volts
	• Not for in-wall use
Compliances:	• UL Wires Misc. (UL: 120V)
Packaging:	• 1000' (305 m) Spools
	• 500' (152 m) Spools
	Other put-ups available- consult Customer Service
Technical Specifications 4' Carol Brand Electrical Wire Center	
3' Carol Brand Electrical Wire Center	
Unit Conversion Factors	
Cable Design Equations - Balanced Pair	
Insulation and Jacket Properties	
Temperature Conversion Chart	
Decimal and Unit Conversion Factors	
Cable Design Equations - Braid Shield	
AWG Conductor Chart	
Conduit Capacity Chart	
<u>Cable Design Equations - Coaxial Cable</u>	
Engineering Prefixes	
Coax Connector Cross Reference	

Glossary



## CAROL BRAND