

Product SKU: C1362.18.90

Product Description: Speaker Wire, UL Listed (Wires, Misc.) 120V max., No. of Conductors: 2, Gauge Size (AWG): 22,

Conductor/Strands: 7/30, Jacket: Premium Grade PVC - Clear - 500 Ft. Spool

Product Category: Electronics - Special Applications - Audio, Video, and Entertainment Cable - Speaker Wire - Clear



Product Construction:

Conductor: • 24 thru 12 AWG fully-annealed 1 bare, 1 tin stranded copper per ASTM B-174

Insulation/Jacket: Premium grade PVC

Product Specification:

No. of Conductors: 2

22

Conductor Size (AWG): • 22

Conductor/Strands: • 7/30

Jacket Color: Clear

Nominal Insulation Thickness

(in):

• 0.020

Nominal Insulation Thickness

(mm):

0.51

Nominal Outside Diameter (in): • 0.070 x 0.145

Nominal Outside Diameter

(mm):

• 1.77 x 3.68

Standard Packaging: • 500' Spool

Standard Package Quantity: 2

UPC #:	• 079407902972
Put-up:	• 500
SCC-14:	• 50079407902977
Cube:	• 288.903
Weight Per Unit of Measure:	• .0084
ColorOption:	• Clear
Product Information:	
Applications:	Hi-fi and stereo speaker wire
	• Juke boxes
	• Lamps
	• Radios
	 Suggested voltage rating: 120 Volts
	 Not for in-wall use
Compliances:	• UL Wires Misc. (UL: 120V)
Packaging:	• 1000' (305 m) Spools
	• 500' (152 m) Spools
	Other put-ups available- consult Customer Service
The 1 1 1 C 1 1 C 1 1 C 1 1 C 1 1 C 1 1 C 1 1 C 1 1 C 1 1 C 1 1 C 1 1 C 1	
Technical Specifications Unit Conversion Factors	
Cable Design Equations - Balanced Pair	
Insulation and Jacket Properties	
Temperature Conversion Chart	
Decimal and Unit Conversion Factors	
Cable Design Equations - Braid Shield	
AWG Conductor Chart	
Conduit Capacity Chart	
<u>Cable Design Equations - Coaxial Cable</u>	
Engineering Prefixes	
Coax Connector Cross Reference	

Glossary



CAROL BRAND