

Product SKU: C2535.41.10

Product Description: Communication & Control Cable, Multi-Conductor, Foil Shield, UL 2093, NEC Type CL2 and CM (UL) c(UL) CMH, No. of Conductors: 3, Gauge Size (AWG): 18, Conductor/Strands: 10/30, Jacket: Gray PVC, Temperature Range: -20°C to +75°C - Gray - 1000 Ft. Reel

Product Category: Electronics - Communication & Control Cable, Multi-Conductor - Foil Shield, Various Approvals - UL STYLE 2093, CM (UL) c(UL) CMH, 300V - Gray



Product Construction:

- Conductor:
 - 24 thru 12 AWG fully-annealed, solid or stranded tinned copper per ASTM B-33

- Insulation:
 - Premium grade color-coded polyethylene

- Shield:
 - 100% Flexfoil® aluminum/polyester with 25% overlap, foil facing out
 - Stranded tinned copper drain wire

- Jacket:
 - PVC, gray
 - Temperature Range: -20°C to +75°C

Product Specification:

- No. of Conductors:
 - 3

- Conductor Size (AWG):
 - 18

- Conductor/Strands:
 - 16/30

- Jacket Color:
 - Gray

- Nominal Insulation Thickness (in):
 - 0.016

- Nominal Insulation Thickness (mm):
 - 0.41

- Nominal Jacket Thickness (in):
 - 0.020

- Nominal Jacket Thickness (mm):
 - 0.51

Nominal Outside Diameter (in):	<ul style="list-style-type: none"> • 0.219
Nominal Outside Diameter (mm):	<ul style="list-style-type: none"> • 5.56
Nominal Capacitance (pF/ft A):	<ul style="list-style-type: none"> • 22.0
Nominal Capacitance (pF/ft B):	<ul style="list-style-type: none"> • 40.0
Standard Packaging:	<ul style="list-style-type: none"> • 1000' Non-returnable Wood Reels
Standard Package Quantity:	<ul style="list-style-type: none"> • 1
UPC #:	<ul style="list-style-type: none"> • 079407715725
Footnote:	<ul style="list-style-type: none"> • Nominal Cap. A: Capacitance between conductors • Nominal Cap. B: Capacitance between one conductor and other conductors connected to shield
Put-up:	<ul style="list-style-type: none"> • 1000
SCC-14:	<ul style="list-style-type: none"> • 50079407715722
Cube:	<ul style="list-style-type: none"> • 1573.9125
Weight Per Unit of Measure:	<ul style="list-style-type: none"> • .03
ColorOption:	<ul style="list-style-type: none"> • Gray

Product Information:

Applications:	<ul style="list-style-type: none"> • Broadcast and sound systems • Computers • Industrial equipment control • Recording studios and sound stages • Suggested voltage rating: 300 Volts
Compliances:	<ul style="list-style-type: none"> • UL Style 2093 (UL: 60°C, 300V) • CM(UL) c(UL) CMH, 300V

Features:

- 25% shield overlap provides excellent shielding efficiency
- Excellent electrical properties
- Good flexibility
- Superior shielding effectiveness

Packaging:

- 1000' (305 m) Spools or Reels
- 500' (152 m) Spools or Reels
- Other put-ups available- consult Customer Service

Reference Charts

[Color Code Chart](#)

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)

Designed to Meet
UL Vertical Tray
Flame Test

Underwriters Laboratories Inc.



CMG
Certified
Canadian Standard Association



**CAROL
BRAND**