

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 5060/30C
Page 1 of 2 Pages

Issue: 10
Issue Date: 1/29/2008
Effective Date: 3/1/2008

A. Construction

Diameters

- 1) Component 1 30 X 1 COND
- a) Conductor 20 (7/28) AWG TC
- b) Insulation 0.016" Wall, Nom. PVC 0.070
- (1) Color Code Alpha Wire Color Code D

| Cond | Color | Cond | Color | Cond | Color |
|------|--------|------|--------------|------|--------------------|
| 1 | BLACK | 11 | PINK | 21 | WHITE/BROWN |
| 2 | RED | 12 | TAN | 22 | WHITE/ORANGE |
| 3 | WHITE | 13 | RED/GREEN | 23 | WHITE/GRAY |
| 4 | GREEN | 14 | RED/YELLOW | 24 | WHITE/VIOLET |
| 5 | ORANGE | 15 | RED/BLACK | 25 | WHITE/BLACK/RED |
| 6 | BLUE | 16 | WHITE/BLACK | 26 | WHITE/BLACK/GREEN |
| 7 | BROWN | 17 | WHITE/RED | 27 | WHITE/BLACK/YELLOW |
| 8 | YELLOW | 18 | WHITE/GREEN | 28 | WHITE/BLACK/BLUE |
| 9 | VIOLET | 19 | WHITE/YELLOW | 29 | WHITE/BLACK/BROWN |
| 10 | GRAY | 20 | WHITE/BLUE | 30 | WHITE/BLACK/ORANGE |

- 2) Cable Assembly 30 Components Cabled
- a) Twists: 2.3 Twists/foot (min)
- b) Core Wrap Nonwoven Polyester Tape, 25% Overlap, Min.
- 3) Jacket 0.032" Wall, Nom.,PVC 0.517 (0.539 Max.)
- a) Color(s) Gray, Black, Yellow, Orange, Blue, Green, Red, Sand Beige, White
- b) Ripcord 1 End 810 Denier Nylon
- c) Print ALPHA WIRE-* P/N 5060/30C 30C 20 AWG

XTRAGUARD 1 XTREME PERFORMANCE FOR XTREME ENVIRONMENTS - 105C (UL) TYPE CM OR AWM 2464 VW-1
--- LLXXXXXX CSA 105C TYPE CMG FT4 CE
ROHS <SEQ FOOTAGE>

* = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

- 1) UL
 - a) Component 1 AWM/STYLE1569 105°C / 300V
 - b) Overall AWM/STYLE2464 80°C / 300V
 - CM 105°C
 - VW-1
- 2) CSA International CMG 105°C
- FT4

3) EU Directive 2002/95/EC(RoHS):
All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.

4) California Proposition 65: The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

5) CE: LVD 73/23/EEC Amendment 93/68/EEC

C. Physical & Mechanical Properties

- 1) Temperature Range -20 to 105°C
- 2) Bend Radius 10X Cable Diameter
- 3) Pull Tension 262 Lbs, Maximum
- 4) Sunlight Resistance Yes

D. Electrical Properties

(For Engineering purposes only)

- 1) Voltage Rating 300 V_{RMS}
- 2) Capacitance 30 pf/ft @1 kHz, Nominal Conductor to Conductor
- 3) Inductance 0.19 µH/ft, Nominal
- 4) Conductor DCR 10.4 Ω/1000ft @20°C, Nominal

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 5060/30C
Page 2 of 2 Pages

Issue: 10
Issue Date: 1/29/2008
Effective Date: 3/1/2008

E. Other

- 1) Packaging
 - a) 1000 FT
 - b) 500 FT
 - c) 100 FT
 - d) Bulk(Made-to-order)

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure the accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.