

ALPHA WIRE COMPANY

CUSTOMER PRODUCT SPECIFICATION

Part Number: 5180/20C
Page 1 of 2 Pages

Issue: 10
Issue Date: 1/29/2008
Effective Date: 3/1/2008

A. Construction

Diameters

- | | | |
|----------------|-------------------------|-------|
| 1) Component 1 | 20 X 1 COND | |
| a) Conductor | 16 (19/.0117) AWG TC | |
| b) Insulation | 0.016" Wall, Nom. PVC | 0.091 |
| (1) Color Code | Alpha Wire Color Code D | |

Cond	Color	Cond	Color	Cond	Color
1	BLACK	8	YELLOW	15	RED/BLACK
2	RED	9	VIOLET	16	WHITE/BLACK
3	WHITE	10	GRAY	17	WHITE/RED
4	GREEN	11	PINK	18	WHITE/GREEN
5	ORANGE	12	TAN	19	WHITE/YELLOW
6	BLUE	13	RED/GREEN	20	WHITE/BLUE
7	BROWN	14	RED/YELLOW		

- | | |
|-------------------|--|
| 2) Cable Assembly | 20 Components Cabled |
| a) Twists: | 2.2 Twists/foot (min) |
| b) Core Wrap | Nonwoven Polyester Tape, 25% Overlap, Min. |
| 3) Shield: | A/P/A Tape, 25% Overlap, Min. |
| a) Drain Wire | 16 (19/.0117) AWG TC |
| b) Braid | TC, 70% Coverage, Min. |
| 4) Jacket | 0.053" Wall, Nom., PVC |
| a) Color(s) | Gray, Black, Yellow, Orange, Blue, Green, Red, Sand Beige, White |
| b) Ripcord | 1 End 810 Denier Nylon |
| c) Print | ALPHA WIRE-* P/N 5180/20C 20C 16 AWG |

0.617 (0.640 Max.)

XTRAGUARD 1 XTREME PERFORMANCE FOR XTREME ENVIRONMENTS - SHIELDED 105C (UL) TYPE CM OR AWM 2464 VW-1 --- LLXXXXXX CSA 105C TYPE CMG FT4

CE ROHS <SEQ FOOTAGE>

* = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

- | | |
|-----------------------------------|---------------|
| 1) UL | |
| a) Component 1 | AWM/STYLE1569 |
| b) Overall | AWM/STYLE2464 |
| | CM |
| | VW-1 |
| 2) CSA International | CMG |
| | FT4 |
| 3) EU Directive 2002/95/EC(RoHS): | |

105°C / 300V

80°C / 300V

105°C

105°C

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.

- | | |
|-------------------------------|--|
| 4) California Proposition 65: | The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65. |
| 5) CE: | LVD 73/23/EEC Amendment 93/68/EEC |

C. Physical & Mechanical Properties

- | | |
|------------------------|--------------------|
| 1) Temperature Range | -20 to 105°C |
| 2) Bend Radius | 10X Cable Diameter |
| 3) Pull Tension | 438 Lbs, Maximum |
| 4) Sunlight Resistance | Yes |

D. Electrical Properties

(For Engineering purposes only)

- | | |
|-----------------------|---|
| 1) Voltage Rating | 300 V _{RMS} |
| 2) Capacitance | 57 pf/ft @1 kHz, Nominal Conductor to Conductor |
| 3) Ground Capacitance | 103 pf/ft @1 kHz, Nominal |
| 4) Inductance | 0.17 µH/ft, Nominal |

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

711 Lidgerwood Ave Elizabeth, NJ 07207-0711

Toll Free 1-800-52 ALPHA • T: 1-908-925-8000 • F: 908-925-5411 • Email: info@alphawire.com
www.xtraguard.com • www.alphawire.com

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 5180/20C
Page 2 of 2 Pages

Issue: 10
Issue Date: 1/29/2008
Effective Date: 3/1/2008

- 5) Conductor DCR 4.4 Ω /1000ft @20°C, Nominal
- 6) OA Shield DCR 1.47 Ω /1000ft @20°C, Nominal

E. Other

- 1) Packaging
 - a) 1000 FT
 - b) 500 FT
 - c) 100 FT
 - d) Bulk(Made-to-order)

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure the accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.