Minimum Quantity

4000

10000

1000

## Data Sheet

## Monolithic Ceramic Capacitors (Reverse Geometry Low ESL Type) LLL185R71E103MA01 (0306, X7R, 10000pF, 25Vdc) :: packaging code RoHS regulation conformity parts

(in mm)

Packaging

180mm Embossed Tape

330mm Embossed Tape

Bulk(Bag)

'LLL/LLA/LLM Series Specification and Test Methods (1)'

Packaging

Code

L

κ

В

Please refer to

PDF file.

Specifications

0.8mm±0.1mm

1.6mm±0.1mm

0.5mm±0.1mm

Spec

X7R (EIA), ±15%

10000pF

±20%

25Vdc

• This data sheet is applied for CHIP MONOLITHIC CERAMIC CAPACITOR used for General Electronics equipment for your design.

## <Notice>

Dimensions

Rated Value

Tenperature Char.

Capacitance

Capacitance Change

**Rated Voltage** 

Length L

Width W

Thickness T

Murata PN Code

R7

103

М

1E

• Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin melting point is used. Please confirm the solderability of Tin plating termination chip before use.

• Use of Sn-Zn based solder will deteriorate reliability of MLCC. Please check with our sales representatives for the use of Sn-Zn based solder in advance.

The RoHS compliance means that we judge from EU Directive 2002/95/EC the products do not contain lead, cadmium, mercury, hexavalent chromium, PBB and PBDE, except exemptions stated in EU Directive 2002/95/EC annex and impurities existing in natural world.
This statement does not insure the compliance of any of the listed parts with any laws or legal imperatives developed by any EU members

individually with regards to the RoHS Directive.

## A Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

