



Industrial and Commercial

G84-4400 Ultralim Series Keyboards



Durable Ultralim Keyboards with Mechanical Keyswitch Technology for Industrial and Commercial Applications



Main Applications

- Rack Mount Systems
- Airlines
- Banking
- Education/Schools
- Manufacturing
- Medical Equipment
- Automotive Equipment
- Office/Data Entry
- White Box PCs
- Field Services
- Test Equipment
- Kiosk Applications
- POS/POT
- Transport

Key Features

- Mechanical Keyswitches are Rated at 50 Million Actuations to Withstand Harsh Environments and Ensure Long Product Lifetime
- Size-reduced QWERTY Key Layout in Ultralim 15" Form Factor Combines Maximal Space Efficiency with Comfortable Alphanumeric Data Entry
- "FN-Key" for Easy Access of Integrated Numeric Area Ensures Complete Function Support as with Full Size Keyboards
- All Available with PS/2 and USB Interface.
- Ultraflat Optical Trackball for Easy Cursor Navigation at Minimized Space
- "Non-Windows" Key Layout

Main Part Numbers

G84-4400PUBUS-0

Light grey 15" ultralim USB keyboard with mechanical trackball. US space reduced 83 position key layout without 'Windows keys', 2 PS/2 connectors. Mechanical keyswitches with tampoprinted keycaps.

G84-4420LPBEU-2

Black 15" ultralim PS/2 keyboard with optical trackball. US space reduced 83 position key layout without 'Windows keys', 2 PS/2 connectors. Mechanical keyswitches with laser etched keycaps.

G84-4420LUBEU-2

Black 15" ultralim USB keyboard with optical trackball. US space reduced 83 position key layout. Mechanical keyswitches with laser etched keycaps.

All models available in light grey and black.

Additional product versions on request.

Industrial and Commercial

G84-4400 Ultrathin Series Keyboards

Part Number Legend

G84-4420LUBEU-2



Technical Data

Interface

PS/2, USB

Current Input

max. 100 mA

Trackball

Diameter: 16mm

Two switch-activated mouse buttons

Mechanical and optical versions available.

Cable Length

Approx. 1.75 m

Key Layout

Sized reduced 83 key layout

Weight (without/with packaging)

0.6/0.7 kg

Dimension

370 x 139 x 20 mm (keyboard)

372 x 141 x 22 mm (packaging)

Packaging Units

21 per master carton

12 master cartons per pallet

Keyswitch Lifetime

50 million operations

Storage Temperature

-20°C to 60°C

Operating Temperature

0°C to 50°C

Approvals

cURus, FCC, CE, VDE, C-Tick, VCCI,
GOST-R (PS/2 version also: RRL, BSMI)

Delivery Volume

Keyboard, Quick Guide,

Warranty

2 years

For information on repairs or
warranty status contact:

Cherry Technical Support

Phone: 800.510.1689

E-Mail: keyboardsupport@cherrycorp.com

Contact

Call, fax or visit our
website for more information.

Cherry Electrical Products

11200 88th Avenue
Pleasant Prairie, WI 53158

Phone: 262.942.6500

Web: www.cherrycorp.com

E-Mail: sales@cherrycorp.com

Fax: 262.942.6566

The manufacturer accepts no
liability for errors or non-availability,
and reserves the right to change
specifications without prior notice.

Technical data relates to product
specifications only. Features may
differ from those described.
Only drawings combined with
product specifications shall be
deemed binding.

Last Update: 10/15/08