Pomona®

Ø .165
(4,19)

.53
(13,46)

□ .250
(6,35)

1.07
(27,2)

.36
(9,2)

Ø.09
(2,4)

FEATURES:
- Threaded two piece design allows wires to be soldered to the banana plug.
- Beryllium Copper spring offers long insertion life.
- Compatible with 18 to 22 AWG wire.
- Available in six colors.

MATERIAL:
Banana Plug: Body - Brass, Nickel Plated

Spring - Beryllium Copper, Nickel Plated

Insulator: Nylon

RATINGS:
Operating Voltage: 500 VRMS

Current: 5 Amperes

ORDERING INFORMATION: Model 5936-*

* = Color, Standard Colors: -0 Black, -2 Red, -4 Yellow, -5 Green, -6 Blue, -9 White

Sold unassembled in packs of 10 per color.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (,51 mm), .xxx = ± .005" (,127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

6/9/99

SY/EH/LS

C:\Laura Goldberg\FlukeDataSheet\d5936_1_01.doc

**Sales: 800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060**

Pomona*ACCESS* **90**___   (800) 444-6785 or (425) 446-6010
More drawings available at www.pomonaelectronics.com

Page 1 of 1