



- Specifications:
1. Insulation Resistance: 100MOhms min. (initial)
  2. Contact Resistance (initial): 30mOhm max at 100mA(max) 1KHz.
  3. Dielectric Withstand Voltage: AC 500V, 60Hz for 1 minute.
  4. Insertion Force: 3Kgs max. Extraction Force: 0.08Kgs min.
  5. Humidity Test: 40±2. 90~95%, 48 hours.

Color Index	Part No.	Finish
	RCP-021	Black
	RCP-022	Red
	RCP-023	White
	RCP-024	Yellow
	RCP-025	Blue
	RCP-026	Green

No.	Description	Material	Qty	Finish
5	Earth Terminal	Brass	1	Nickel Plated
4	Tip Terminal	Brass	1	Nickel Plated
3	Barrel	Brass	1	Nickel Plated
2	Cover	ABS	1	Black Color
1	Barrel Housing	ABS	1	See Color Index



**CUI INC**

9615 SW Allen, Suite 103  
 Beaverton, OR 97005  
 Phone: (503) 643-4899  
 800-275-4899  
 Fax: (503) 372-1266  
 Website: [www.cui.com](http://www.cui.com)

TITLE: RCA Plug, Modular, Plastic Handle w/Strain Relief

PART NO. RCP-02X UNITS: Millimeters

DRAWN BY: Todd R. White APPROVED BY: SCALE: 2x