



NO.	PART NAME	MATERIAL	PLATING	REMARKS
1	HOUSING	POLYAMIDE		UL94V0
2	BOTTOM COVER	POLYAMIDE		UL94V0
3	RING TERMINAL	Cu-Ti	GOLD FLASH	25 MICRONS
4	SHUNT TERMINAL	BRASS	GOLD FLASH	30 MICRONS
5	TIP TERMINAL	Cu-Ti	GOLD FLASH	25 MICRONS
6	SLEEVE (EARTH) TERMINAL	PBS	GOLD FLASH	30 MICRONS



9815 SW Allen, Suite 109
 Beaverton, OR 97005
 Phone: (503) 643-4899
 800-275-4899
 Fax: (503) 372-1286
 Website: www.cui.com

- SPECIFICATIONS:**
1. RATED VOLTAGE-16 VDC
 2. RATED CURRENT-300 mA
 3. CONTACT RESISTANCE-100 MOHMS OR LESS UNDER ALL CONDITIONS, INCLUDING AFTER LIFE TESTING.
 4. INSULATION RESISTANCE-100 MOHMS OR GREATER AT 500 VDC.
 5. DIELECTRIC WITHSTAND VOLTAGE-500 VAC RMS FOR 1 MINUTE.

