


HOLE LAYOUT
(TOP VIEW)



SPECIFICATIONS:
 RATING: 12V DC @ 1A
 CONTACT RESISTANCE:
 30 MOHMS MAX
 INSULATION RESISTANCE:
 100 MOHMS MIN @ 500V DC
 WITHSTAND VOLTAGE:
 500V AC FOR 1 MINUTE
 LIFE: 5,000 CYCLES

| NO. | DESCRIPTION | MATERIAL | QTY | FINISH |
|-----|----------------|----------------------|-----|---------------|
| 7 | HOUSING | PBT | 1 | BLACK COLOR |
| 6 | BARREL | BRASS | 1 | NICKEL PLATED |
| 5 | TIP SPRING | 0.25T TiCuR1-M-EH | 1 | SILVER PLATED |
| 4 | BREAK TERMINAL | 0.3T BRASS | 1 | SILVER PLATED |
| 3 | BREAK TERMINAL | 0.3T BRASS | 1 | SILVER PLATED |
| 2 | RING SPRING | 0.2T TiCuR1-M-EH | 1 | SILVER PLATED |
| 1 | EARTH TERMINAL | 0.2T PHOSPHOR BRONZE | 1 | SILVER PLATED |

cui inc
 9615 SW Allen, Suite 103
 Beaverton, OR 97005
 Phone: (503) 643-4899
 800-275-4899
 Fax: (503) 372-1266
 Website: www.cui.com

PC FILE NAME: SJ3525NG.DWG
 COPYRIGHT 1997 BY CUI INC.

TITLE: **3.5mm AUDIO JACK-STEREO**

PART NO. SJ-3525NG UNITS: MILLIMETERS
 DRAWN BY: Todd R. White APPROVED BY: SCALE: 3X