


DO NOT SCALE FROM THIS PRINT



LEAD STYLE	"A" (POST)	"B" (OAL)	"C"
-01	.126 [3.20]	.302 [7.67]	.100 [2.54]
-04	.075 [1.91]	.255 [6.48]	.100 [2.54]
-05	.065 [1.65]	.323 [8.20]	.080 [2.03]
-06	.168 [4.27]	.476 [12.09]	.100 [2.54]

PATENT NUMBERS
5713755 / 5961339

UNLESS OTHERWISE NOTED TOLERANCES ARE:
 DIMENSIONS ARE IN INCHES
 ONE PLACE DECIMALS ±.1 [2.5] THREE PLACE DECIMALS ±.005 [.13] ANGLES ± 2°
 TWO PLACE DECIMALS ±.010 [25] FOUR PLACE DECIMALS ±.0020 [05]

TITLE: 2mm TERMINAL STRIP ASSEMBLY (S/M)
 DWG NO: TMM-1XX-XX-XX-X-SM-XX-X
 SHEET 1 OF 2

TMM-1XX-XX-XX-X-SM-XX-X

NO. OF POSITIONS PER ROW
 -02 THRU -40

TERMINAL SPEC
 -01: USE T-1S13-07-X-2
 -04: USE T-1S13-04-X-2
 -05: USE T-1S13-21-X-2
 -06: USE T-1S13-08-X-2 (SEE NOTE 8)

PLATING SPECIFICATION
 -G: GOLD (SPECIFY -G IN TERMINAL SUFFIX -X)
 -T: TIN (SPECIFY -T IN TERMINAL SUFFIX -X)
 -S: SELECTIVE (SPECIFY -S IN TERMINAL SUFFIX -X)
 -L: SELECTIVE (SPECIFY -L IN TERMINAL SUFFIX -X)
 -F: FLASH SELECTIVE GOLD (SPECIFY -F IN TERMINAL SUFFIX -X)
 -H: HEAVY GOLD (SPECIFY -H IN TERMINAL SUFFIX -X)
 -SM: HEAVY GOLD SELECTIVE, MATTE TIN TAIL (SPECIFY -S IN TERMINAL SUFFIX -X)
 -TM: MATTE TIN (SPECIFY -T IN TERMINAL SUFFIX -X)
 -LM: LIGHT GOLD SELECTIVE, MATTE TIN TAIL (SPECIFY -L IN TERMINAL SUFFIX -X)
 -FM: FLASH GOLD SELECTIVE, MATTE TIN TAIL (SPECIFY -F IN TERMINAL SUFFIX -X)




OPTION
 -P: PICK & PLACE PAD (AVAILABLE ON POSITIONS -03 THRU -40) (SEE FIG 2)
 -M: METAL PICK & PLACE PAD (SEE FIG 2)(4 POS. MIN) (NOT RECOMMENDED ON -T & -TM PLATING)
 -A: ALIGNMENT PIN (SEE FIG 3) (5 POS. PER ROW MINIMUM) (NOT AVAILABLE ON SINGLE BODY SPECIFICATION)
 -TR: TAPE & REEL (AVAILABLE ON POS -03 THRU 40)

OPTION
 POLARIZED
 SPECIFY POS -XX AS POS TO BE OMITTED

OPTION
 -SM: SURFACE MOUNT

BODY SPECIFICATION
 -S: SINGLE (TMM-50-S)
 -D: DOUBLE (TMM-50-D)

NOTES:
 1.) MAX. PIN ROTATION IN BODY: 2°
 2.) PUSHOUT FORCE SHALL BE 1 lb MIN.
 3.) (C) REPRESENTS A CRITICAL DIMENSION.
 4.) ALL DIMENSIONS IN BRACKETS [] TO BE MILLIMETERS.
 5.) PACKAGE POSITIONS 03-40 IN TUBES; LAYER PACKAGE -02 POSITION.
 6.) .050 [1.27] DIMS TO BE CHECKED AT BEND RADIUS, NOT AT END OF PIN
 7.) NOTE DELETED
 8.) SHEAR TAILS FOR -05 & -06 LEAD STYLE.
 9.) NO BANDOLIER MARKS ARE ALLOWED IN THE POST AREA.
 10.) NOTE DELETED
 11.) MAX. CUT FLASH: .010 [.25]



PROPRIETARY NOTE
 THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC INC.

MATERIAL:
 BODIES: LCP
 COLOR: BLACK
 TERMINALS: PHOSPHER BRONZE

EXISPROD ASSEMBLY\2mm TMM-SM

samtec

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
 PHONE (812) 944-6733 P.O. BOX 1147
 CODE 55322

MADE BY: REIDINGER 5-22-91
 CHECKED BY: MCCARTIN

APPROVAL: DEM

TMM-1XX-XX-XX-X-SM-XX-X
 SHEET 1 OF 2