



RECOMMENDED PCB LAYOUT

X ±	X* ± 1*
X ± 0.10	X* ± 0.5*
XX ± 0.05	XX* ±
XXX ±	XXX* ±

UNITS	MM	NAME (INTENDED USE)	
MAT'L		PART NO. (INTENDED USE)	
FINISH		APPD:	
QTY		CHKD:	
		DRWN: N. Doanue	9/23/97
TITLE:		PART NO. TRXB092DKHN-1330/T26	
SULLINS ELECTRONICS CORP		SCALE	SHEET 1 OF 1
		REV	A

PLASTIC POST -1330

ENVIRONMENTAL
 TEMPERATURE RANGE: -55° TO +85.
 NO PART MARKINGS

GOLD PLATING
 REPLACE "*" IN THE PART NUMBER:
 W = SELECTIVE GOLD FLASH
 Z = SELECTIVE 100μ" GOLD
 X = SELECTIVE 30μ" GOLD

MATERIAL
 INSULATOR: GLASS-REINFORCED THERMOPLASTIC,
 U194V-0 RATED.
 CONTACT: COPPER ALLOY.
 PLATING: MATING AREA- GOLD,
 SOLDER AREA- TIN/LEAD.

ELECTRICAL
 VOLTAGE RATING: 250 VAC RMS.
 CURRENT RATING: 3 AMP.
 INSULATION RESISTANCE: 1,000 MEGOHMS MIN.
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.

MECHANICAL
 CONTACT RETENTION: 460 GRAMS MIN PER CONTACT.
 INSERTION FORCE: 230 GRAMS MAX PER CONTACT PAR.
 WITHDRAWAL FORCE: 15 GRAMS MIN PER CONTACT PAR

REV	DESCRIPTION	BY	DATE
A	Added position 1 indicators	BC	06-03-03