



- WILL ACCEPT (12) MULTIMATE AND (4) TYPE XII PIN CONTACTS.
  - CAVITY IDENTIFICATION ON FRONT AND REAR FACE.
  - NO. 4 FASTENERS RECOMMENDED FOR MOUNTING.
  - THIS CONNECTOR WILL ACCEPT INSULATION DIAMETERS UP TO 3.81 [.150].
- HOUSING: NYLON, BLACK.
  - PERIPHERAL SEAL: ELASTOMER, GRAY.
  - PERMANENT WHITE MARKED OR WHITE INK STAMPED CAVITY IDENTIFICATION.
  - HOUSING: NYLON, RED.
  - PERIPHERAL SEAL: ELASTOMER, GRAY.
  - WHITE DOT NEAR POSITION 1 ON WIRE ENTRY FACE.

PRELIMINARY	8	-	YES	A	1-207486-1
PRELIMINARY	5	-	YES	A	207486-9
	5	-	YES	A	207486-7
	4	4	YES	A	207486-6
	5	-	YES	A	207486-5
	5	-	NO	B	207486-2
	5	-	NO	A	207486-1
NOTES	THREADED INSERTS	PERIPHERAL SEAL	SEE DETAIL	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN M BINNER 05/26/94  
 CHK R STONE 6-23-94

**tyco** Electronics  
 Tyco Electronics Corporation  
 Harrisburg, PA 17105-3608

PRODUCT SPEC: 108-10024  
 APPLICATION SPEC: -

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 207486  
 WEIGHT: -

CUSTOMER DRAWING SCALE: 2:1 SHEET: 1 OF 1 REV: P1